

INDUSTRIAL COMPONENT DATA

AXL SE PD16 GND 1337224 PHOENIX CONTACT Axioline Smart Elements, Potential Distribution Module, GND, Protect..

Brand: PHOENIX CONTACT | Manufacturer Part Number: AXL SE PD16 GND



Manufacturer	PHOENIX CONTACT
MPN / Reference	AXL SE PD16 GND
Catalog number	1337224
Category	Fieldbus, decentr. periphery - power supply/segment module
Minimum order	1 Pcs
Document ID	EO-11DECBD233
Generated	2026-08-02

Product Overview

Axioline Smart Elements, Potential Distribution Module, GND, Protection Rating: IP20
Axioline Smart Elements, Potential distribution module, GND, degree of protection: IP20

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > I/O

Additional Product Information

Technical data
Dimensions
Dimensional drawing
Width 14.9 mm
Height 62.2 mm
Depth 62 mm
Interfaces
Smart Element interface
Number of interfaces 1
Connection method Card edge connector
Transmission speed See system in which you use the Smart Element.
System properties
Module
ID code (hex) none
Process data channel 0 bit
Input address area 0 Byte (All systems except PROFIBUS)
1 Byte (PROFIBUS)
Output address area 0 Byte

Required parameter data 1 Byte
Required configuration data 6 Byte
Product propertiesType modular
Product type I/O component
Product family Axioline Smart Elements
Mounting position See the system in which the Smart Element is used.
Insulation characteristics
Overvoltage category II (IEC 60664-1, EN 60664-1)
Pollution degree 2 (IEC 60664-1, EN 60664-1)
Electrical propertiesPotentials: Communications power supply of the Smart Elements (USE)
Supply voltage using card edge connectors
Potentials: I/O supply (UP)
Supply voltage 24 V DC (using card edge connectors)
Supply voltage range 19.2 V DC ... 30 V DC (including all tolerances, including ripple)
Current draw max. 0 mA
Current consumption min. 0 mA (without connected peripherals)
Power consumption max. 0 mW
Protective circuit Surge protection; See the system in which the Smart Element is used.
Reverse polarity protection; Polarity protection diode
Electrical isolation/isolation of the voltage ranges
Test voltage: Communications supply / 24 V supply (I/O) 500 V AC, 50 Hz, 1 min.
Test voltage: Communications supply / fu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AXL SE PD16 GND with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.