


INDUSTRIAL COMPONENT DATA

PT 2XEX(I)-BE 2839279 PHOENIX CONTACT Surge protection base element

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 2XEX(I)-BE



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 2XEX(I)-BE
Catalog number	2839279
Category	Accessories/spare parts for surge protection data networks/MCR-te
Minimum order	10 Pcs
Document ID	EO-57CBC68199
Generated	2026-07-31

Product Overview

Surge protection base element

PT plug-in protection base element with protection circuit for two two-conductor EEx ia signal circuits without earth potential.
Mounting on NS 35/7.5 and NS 35/15, housing width: 17.5 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)
--------------	---------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2839279

Packing unit 10 pc

Catalog page Page 132 (C-4-2017)

GTIN 4017918182885

Weight per Piece (excluding packing) 62.430 g

Custom tariff number 85363010

Country of origin DE (Germany)

Dimensions

Height 90 mm

Width 17.7 mm

Depth 51.5 mm (incl. DIN rail 7.5 mm)

Horizontal pitch 1 Div.

Ambient conditions

Ambient temperature (operation) -40 °C ... 85 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Altitude ≤ 2000 m (amsl (above mean sea level))

Degree of protection IP20

General

Housing material PA 6.6

Flammability rating according to UL 94 V-0

Color sky blue RAL 5015

Mounting type DIN rail: 35 mm

Type Base element, DIN rail mounting

Number of positions 4

Protective circuit

Nominal voltage UN 24 V DC

Maximum continuous voltage UC 30 V DC

21 V AC

Rated current 325 mA (≤40 °C)

Resistance in series 2.2 Ω ±10 %

Surge protection fault message none

Max. required back-up fuse 315 mA (T)

Connection data

Connection method Screw connection

Screw thread M3

Tightening torque 0.5 Nm

Stripping length 8 mm

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section solid 0.2 mm² ... 4 mm²

Conductor cross section AWG 24 ... 12

Standards and Regulations

Standards/specifications EN 61643-21 A2:2013

EN 60079-0 2012

EN 60079-11 2012

EN 60079-26 2007

IEC 60079-0 2011

IEC 60079-11 2011

IEC 60079-26 2006

General

Maximum inner capacitance Ci 1.3 nF

Max. internal inductance Li 1 µH

Maximum inner time factor (Ri/Li) ≤ 0.2 µs

Max. input current Ii...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 2XEX(I)-BE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.