


INDUSTRIAL COMPONENT DATA

CB 1/10-1/10 UT-BE 2801305 PHOENIX CONTACT Base element

Brand: PHOENIX CONTACT | Manufacturer Part Number: CB 1/10-1/10 UT-BE



Manufacturer	PHOENIX CONTACT
MPN / Reference	CB 1/10-1/10 UT-BE
Catalog number	2801305
Category	Device circuit breaker
Minimum order	10 Pcs
Document ID	EO-65EAEB8C33
Generated	2026-08-03

Product Overview

Base element

Base element with screw connection technology for CB apparatus protection switch ...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Over Current Protection

Additional Product Information

Key Commercial Data

Orderkey 2801305

Packing unit 10 pc

Minimum order quantity 10 pc

Catalog page Page 331 (C-4-2017)

GTIN 4046356769198

Weight per Piece (excluding packing) 39.420 g

Custom tariff number 85366990

Country of origin ID (Indonesia)

Dimensions

Height 90.8 mm

Width 12.3 mm

Depth 70 mm

Ambient conditions

Ambient temperature (operation) -30 °C ... 60 °C

Degree of protection IP30 (Actuation area)

General

Flammability rating according to UL 94 V0

Mounting type DIN rail: 35 mm

Color gray

Type Base element, DIN rail mounting

Electrical data

Nominal voltage UN 277 V

Rated surge voltage 2.5 kV

Rated voltage 277 V (AC)

80 V (DC)

Rated current IN 16 A

Rated insulation voltage Ui 277 V AC

Insertion/withdrawal cycles 100

Connection data

Connection name Connection 1

Connection method Screw connection

Stripping length 10 mm

Conductor cross section flexible min. 0.5 mm²

Conductor cross section flexible max. 16 mm²

Conductor cross section solid min. 0.5 mm²

Conductor cross section solid max. 16 mm²

Conductor cross section AWG min. 20

Conductor cross section AWG max. 6

Connection name Connection 2

Connection method Screw connection

Stripping length 10 mm

Conductor cross section flexible min. 0.5 mm²

Conductor cross section flexible max. 16 mm²

Conductor cross section solid min. 0.5 mm²

Conductor cross section solid max. 16 mm²

Conductor cross section AWG min. 20

Conductor cross section AWG max. 6

Connection name Connection 12/11/14

Connection method Screw connection

Stripping len...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CB 1/10-1/10 UT-BE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.