

INDUSTRIAL COMPONENT DATA

BC 107,6-KIT-RPI-7035 1311013 PHOENIX CONTACT Empty Case, Rail Mount, Light Grey 7035, Clear Swivel Cover, f..

Brand: PHOENIX CONTACT | Manufacturer Part Number: BC 107,6-KIT-RPI-7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	BC 107,6-KIT-RPI-7035
Catalog number	1311013
Category	Electronic enclosure
Minimum order	1 Pcs
Document ID	EO-6DB03753E1
Generated	2026-08-04

Product Overview

Empty Case, Rail Mount, Light Grey 7035, Clear Swivel Cover, for Raspberry Pi Computers (Suitable for Raspberry Pi A+, B+, B2, B3, B4), Width: 107.6 mm, Height: 89.7 mm, Depth: 60.7 mm

Empty enclosure, DIN rail mounting, light gray (7035), transparent hinged cover, for Raspberry Pi computer (suitable for Raspberry Pi A+, B+, B2, B3, B4), width: 107.6 mm, height: 89.7 mm, depth: 60.7 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Stackable housing set

Type Housing set

Housing type DIN rail housing for use in distribution boards in accordance with DIN 43880

Ventilation openings present yes

Housing series BC

DimensionsDimensional drawing

Width 107.6 mm

Height 89.7 mm

Depth 60.7 mm

Depth from top edge of DIN rail 54.7 mm

Material specificationsColor light grey (7035)

Flammability rating according to UL 94 V0

Insulating material Polycarbonat
Housing material Polycarbonate
Environmental and real-life conditions Power dissipation single housing for 20 °C
Ambient temperature 20 °C
Reduction factor 1
Power dissipation single housing for 30 °C
Ambient temperature 30 °C
Reduction factor 0.84
Power dissipation single housing for 40 °C
Ambient temperature 40 °C
Reduction factor 0.72
Power dissipation single housing for 50 °C
Ambient temperature 50 °C
Reduction factor 0.6
Power dissipation single housing for 60 °C
Ambient temperature 60 °C
Reduction factor 0.48
Power dissipation single housing for 70 °C
Ambient temperature 70 °C
Reduction factor 0.38
Ambient conditions
Max. IP code to attain IP20
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Ambient temperature (storage/transport) -40 °C ... 70 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Relative humidity (storage/transport) 95 %
PCB data Type of PCB mount Latching
Mounting Mounting type DIN rail mounting/wall mounting
Mounting position parallel to the DIN rail
Packaging specifi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BC 107,6-KIT-RPI-7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.