

## INDUSTRIAL COMPONENT DATA

# BC 161,6-KIT-U11-7035 + 6SPTA12 1311011 PHOENIX CONTACT Rail box for use in installation distributors accord..

Brand: PHOENIX CONTACT | Manufacturer Part Number: BC 161,6-KIT-U11-7035 + 6SPTA12



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | PHOENIX CONTACT                 |
| MPN / Reference | BC 161,6-KIT-U11-7035 + 6SPTA12 |
| Catalog number  | 1311011                         |
| Category        | Electronic enclosure            |
| Minimum order   | 1 Pcs                           |
| Document ID     | EO-D71D2AD3F8                   |
| Generated       | 2026-08-06                      |

## Product Overview

Rail box for use in installation distributors according to DIN 43880, for installation on DIN rail, with transparent tilting cover, color: black (Similar RAL 9005), width: 161.6 mm, height: 89.7 mm, depth: 60.7 mm, incl. 6 terminals for printed circuit board, 12 poles, push-in, for 1 mm<sup>2</sup>, nominal current: 9 A, 200 V, Printed circuit board surface: 12600 mm<sup>2</sup>

Rail housing for use in DIN 43880 installation distributors, for DIN rail mounting, with transparent tilting cover, colour: black (9005), width: 161.6 mm, height: 89.7 mm, depth: 60.7 mm, incl. 6 PCB terminals, 12 poles, push-in, for 1 mm<sup>2</sup>, nominal current: 9 A, 200 V, printed circuit board surface: 12600 mm<sup>2</sup>

DIN rail housing for use in distribution boards in accordance with DIN 43880, for mounting on a DIN rail, with transparent hinged cover, color: black (9005), width: 161.6 mm, height: 89.7 mm, depth: 60.7 mm, incl. 6 PCB terminal blocks, 12-pos., Push-in, for 1 mm<sup>2</sup>, nominal current: 9 A, 200 V, PCB surface: 12600 mm<sup>2</sup>

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                |
|--------------|--------------------------------|
| Catalog path | PHOENIX CONTACT > Housing (HS) |
|--------------|--------------------------------|

## Additional Product Information

Technical dataNotesGeneral Please observe the assembly instructions available in the download area.

General The PCB surface specification is for orientation purposes and is based on a basic PCB. The housing can also accommodate several PCBs.

Product propertiesProduct type Stackable housing set

Product family BC 161,6

Number of positions 72

Max. number of positions 72 (pitch: 3.5 mm)

Type for mounting on a DIN rail, with transparent hinged cover  
incl. 6 PCB terminal blocks, 12-pos., Push-in, for 1 mm<sup>2</sup>, nominal current: 9 A, 200 V  
Housing type DIN rail housing for use in distribution boards in accordance with DIN 43880  
Ventilation openings present yes  
Housing series BC  
DimensionsDimensional drawing  
Width 161.6 mm  
Height 89.7 mm  
Depth 60.7 mm  
Depth from top edge of DIN rail 54.7 mm  
Horizontal pitch 9 Div.  
Dimensions 81.54 mm x 157.5 mm (PCB dimensions)  
PCB design  
PCB thickness 1.4 mm ... 1.8 mm  
Material specificationsColor black (9005)  
Color (Housing cover) transparent  
Flammability rating according to UL 94 V0  
Insulating material Polycarbonat  
Housing material Polycarbonate  
Environmental and real-life conditionsAmbient conditions  
Max. IP code to attain IP20  
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)  
Ambient temperature (storage/transport) -40 °C ... 70 °C  
Ambient temperature (assembly) -5 °C ... 100 °C  
Relative humidity (storage/transport) 95 %  
PCB dataNumber of PCB holders 9  
Type of PCB mount Latching  
Total PCB surface 12600 mm<sup>2</sup>  
Thickness...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BC 161,6-KIT-U11-7035 + 6SPTA12 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.