


INDUSTRIAL COMPONENT DATA

BC 161,6 OT U11 KMGY S1193 1054283 PHOENIX CONTACT DIN rail housing for use in distribution boards in accord..

Brand: PHOENIX CONTACT | Manufacturer Part Number: BC 161,6 OT U11 KMGY S1193



Manufacturer	PHOENIX CONTACT
MPN / Reference	BC 161,6 OT U11 KMGY S1193
Catalog number	1054283
Category	Electronic enclosure
Minimum order	250 Pcs
Document ID	EO-EDAE79478E
Generated	2026-08-06

Product Overview

DIN rail housing for use in distribution boards in accordance with DIN 43880, Upper housing part with vents, width: 161.6 mm, height: 89.7 mm, depth: 54.85 mm, color: light gray (7035)

Rail box for use in installation distributors according to DIN 43880, Top of the housing (U11) with ventilation slits, Installation depth of connection technology: 11.1 mm, width: 161.6 mm, height: 89.7 mm, depth: 54.85 mm, colour: light grey (7035)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data

Orderkey 1054283

Packing unit 1

GTIN 4055626689319

Custom tariff number 85472000

Drawings

Dimensions

Ambient conditions

Packaging information

Classifications

Item properties

Material data

[PCB data](#)

[Standards and regulations](#)

[Drawings](#)

[Dimensional drawing](#)

[Back to topItem properties](#)

[Brief article description](#) Upper part of housing

Type BC 161,6 OT U11 KMGY S1193

Order No. 1054283

Housing type DIN rail housing for use in distribution boards in accordance with DIN 43880

Housing series BC

Type Upper housing part with vents

Max. IP code to attain IP20

Mounting type Snap in

Connection levels 1 (Both sides)

Ventilation openings present yes

Max. number of positions 96 (pitch: 2.5 mm)

72 (pitch: 3.5 mm)

54 (pitch: 5 mm)

36 (pitch: 7.5 mm)

[Back to topDimensions](#)

[Dimensional drawing](#)

Width [w] 161.6 mm

Height [h] 89.7 mm

Depth [d] 54.85 mm

[Back to topMaterial data](#)

Color (RAL) light gray (7035)

Flammability rating according to UL 94 V0

Housing material Polycarbonate

[Back to topAmbient conditions](#)

Ambient temperature (storage/transport) -40 °C ... 70 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 100 °C (depending on power dissipation)

Relative humidity (storage/transport) 95 %

[Back to topPCB data](#)

Number of PCB holders 18

Mounting position parallel to the DIN rail

Type of PCB mount Latching

[Back to topPackaging information](#)

Type of packaging packed in cardboard

Pieces per package 10

Denomination packing units Pcs.

Outer pack...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BC 161,6 OT U11 KMGY S1193 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.