

INDUSTRIAL COMPONENT DATA

BC-508X18- 6 GY 5436555 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: BC-508X18-6 GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	BC-508X18-6 GY
Catalog number	5436555
Category	Printed circuit board terminal
Minimum order	100 Pcs
Document ID	EO-4ABCCEA3EA
Generated	2026-08-05

Product Overview

PCB terminal block

Printed circuit board terminal block, rated current: 24 A, rated voltage (III/2): 400 V, rated cross-section: 2.5 mm², number of potentials: 6, number of rows: 1, number of poles per row: 6, article family: BC-X18, pitch: 5.08 mm, connection type: Screw connection with traction capsule, mounting: Wave soldering, conductor connection direction/printed circuit board: 0°, color: gray signals, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, number of solder pins per potential: 1, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

PCB terminal block, nominal current: 24 A, nom. voltage: 400 V, pitch: 5.08 mm, number of positions: 6, connection method: Screw connection with tension sleeve, mounting: Wave soldering, conductor/PCB connection direction: 0 °, color: signal grey

Key Commercial Data

Orderkey 5436555

Packing unit 100 pc

Minimum order quantity 100 pc

Note Made to Order (non-returnable)

GTIN 4046356331180

Weight per Piece (excluding packing) 11.860 g

Custom tariff number 85369010

Country of origin CN (China)

Dimensions

Length [l] 11.2 mm

Pitch 5.08 mm

Dimension a 25.4 mm

Width [w] 30.48 mm

Height 18 mm

Height [h] 21.5 mm

Solder pin [P] 3.5 mm

Hole diameter 1.3 mm

General

Range of articles BC-X18

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 400 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current IN 24 A

Nominal cross section 2.5 mm²

Insulating material PA

Solder pin surface

Flammability rating according to UL 94 V0

Stripping length 7 mm

Number of positions 6

Screw thread M3

Tightening torque, min 0.5 Nm

Tightening torque max 0.6 Nm

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 4 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BC-508X18-6 GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.