

INDUSTRIAL COMPONENT DATA

BC 53,6 DKL R GN 1556475 PHOENIX CONTACT Rail box for use in installation distributors according to DIN 4388..

Brand: PHOENIX CONTACT | Manufacturer Part Number: BC 53,6 DKL R GN



Manufacturer	PHOENIX CONTACT
MPN / Reference	BC 53,6 DKL R GN
Catalog number	1556475
Category	Extruded profile modular housing
Minimum order	100 Pcs
Document ID	EO-1B06BEB301
Generated	2026-08-05

Product Overview

Rail box for use in installation distributors according to DIN 43880, Fitted cover (fixed), width: 53.6 mm, height: 45 mm, depth: 8 mm, colour: green (Similar RAL 6021)

Rail housing for use in installation distributors according to DIN 43880, Recessed cover (fixed), width: 53.6 mm, height: 45 mm, depth: 8 mm

DIN rail housing for use in distribution boards in accordance with DIN 43880, Latching cover (non-detachable), width: 53.6 mm, height: 45 mm, depth: 8 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Technical dataNotesGeneral Refer to the data sheet for the range in the download area.

Product propertiesProduct type Cover

Product family BC DKL R KMGY

Type Latching cover (non-detachable)

Housing type DIN rail housing for use in distribution boards in accordance with DIN 43880

Ventilation openings present no

Housing series BC

Connection dataCross section AWG (converted acc. to IEC)

DimensionsWidth 53.6 mm

Height 45 mm

Depth 8 mm

Material specifications Surface characteristics untreated

Housing material Polycarbonate

Environmental and real-life conditions Ambient conditions

Max. IP code to attain IP20

Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)

Ambient temperature (storage/transport) -40 °C ... 70 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Relative humidity (storage/transport) 95 %

Mounting Mounting type Latching with upper housing part

Mounting position Vertical (horizontal DIN rail)

Packaging specifications Type of packaging Box packaging

ETIM for 1556475 Low-voltage industrial controls and switchgear (EC002779)

Feature Name

Feature Value

Type of enclosure (EF003086)

Closed

Housing connectable (EF003088)

No

Suitable for rail mounting (EF003972)

No

Wall mounting possible (EF003973)

No

With integrated PCB-mounting connection system (EF003087)

No

Material (EF002169)

Other

Surface finishing (EF006569)

Other

Colour (EF000007)

Green

RAL-number (EF000116)

6021

Width (EF000008)

53.6 mm

Height (EF000040)

45 mm

Depth (EF000049)

8 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BC 53,6 DKL R GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.