

INDUSTRIAL COMPONENT DATA

BC 71,6 OT 0111 KMGY MOQ100 1093075 PHOENIX CONTACT

Installation component housing, Upper housing part with ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: BC 71,6 OT 0111 KMGY MOQ100



Manufacturer	PHOENIX CONTACT
MPN / Reference	BC 71,6 OT 0111 KMGY MOQ100
Catalog number	1093075
Category	Extruded profile modular housing
Minimum order	100 Pcs
Document ID	EO-60D3932722
Generated	2026-08-04

Product Overview

Installation component housing, Upper housing part with vents, width: 71.6 mm, height: 89.7 mm, depth: 54.85 mm, color: light gray (7035)

Rail housing for use in installation distributors according to DIN 43880, Top of modular housing, width: 71.6 mm, height: 89.7 mm, depth: 54.85 mm, colour: light grey (7035)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data
 Orderkey 1093075
 Packing unit 1
 GTIN 4055626909738
 Custom tariff number 85389099
 Item properties
 Material data
 PCB data
 Standards and regulations
 Dimensions
 Ambient conditions
 Packaging information

Classifications

Item properties

Brief article description Upper part of housing

Type BC 71,6 OT 0111 KMGY MOQ100

Order No. 1093075

Housing type Installation component housing

Housing series BC

Type Upper housing part with vents

Max. IP code to attain IP20

Mounting type Snap in

Connection levels 1 (Both sides)

Ventilation openings present yes

Max. number of positions 44 (pitch: 2.5 mm)

32 (pitch: 3.5 mm)

24 (pitch: 5 mm)

16 (pitch: 7.5 mm)

Back to topDimensions

Width [w] 71.6 mm

Height [h] 89.7 mm

Depth [d] 54.85 mm

Back to topMaterial data

Color (RAL) light gray (7035)

Flammability rating according to UL 94 V0

Housing material Polycarbonate

Back to topAmbient conditions

Ambient temperature (storage/transport) -40 °C ... 70 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 100 °C (depending on power dissipation)

Relative humidity (storage/transport) 95 %

Back to topPCB data

Number of PCB holders 1

PCB thickness 1.8 mm

Mounting position parallel to the DIN rail

Type of PCB mount Latching

Back to topPackaging information

Pieces per package 20

Denomination packing units Pcs.

Back to topStandards and regulations

Flammability rating according to UL 94 V0

Back to topClassifications

eCI@ss

eCI@ss 6.0 27180800

eCI@ss 7.0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BC 71,6 OT 0111 KMGY MOQ100 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.