


INDUSTRIAL COMPONENT DATA

BC 71,6 OT 1010 KMGY MOQ100 1136628 PHOENIX CONTACT DIN rail housing for use in distribution boards in accor..

Brand: PHOENIX CONTACT | Manufacturer Part Number: BC 71,6 OT 1010 KMGY MOQ100



Manufacturer	PHOENIX CONTACT
MPN / Reference	BC 71,6 OT 1010 KMGY MOQ100
Catalog number	1136628
Category	Extruded profile modular housing
Minimum order	100 Pcs
Document ID	EO-9BDB0D5AD9
Generated	2026-08-06

Product Overview

DIN rail housing for use in distribution boards in accordance with DIN 43880, Upper housing part with vents, width: 71.6 mm, height: 89.7 mm, depth: 54.85 mm, color: light gray (7035)

Rail housing for use in installation distributors according to DIN 43880, Top of modular housing, width: 71.6 mm, height: 89.7 mm, depth: 54.85 mm, colour: light grey (7035)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data

Orderkey 1136628

Packing unit 1

GTIN 4063151073190

Custom tariff number 85389099

Drawings

Dimensions

Ambient conditions

General information

Standards and regulations

Item properties

Material data

[PCB data](#)

[Packaging information](#)

[Classifications](#)

[Drawings](#)

[Dimensional drawing](#)

[Back to topItem properties](#)

[Brief article description](#) Upper part of housing

Type BC 71,6 OT 1010 KMGY MOQ100

Order No. 1136628

Housing type DIN rail housing for use in distribution boards in accordance with DIN 43880

Housing series BC

Type Upper housing part with vents

Max. IP code to attain IP20

Mounting type Snap in

Connection levels 1 (Both sides)

Ventilation openings present yes

Max. number of positions 44 (pitch: 2.5 mm)

32 (pitch: 3.5 mm)

24 (pitch: 5 mm)

16 (pitch: 7.5 mm)

[Back to topDimensions](#)

[Dimensional drawing](#)

Width [w] 71.6 mm

Height [h] 89.7 mm

Depth [d] 54.85 mm

[Back to topMaterial data](#)

Color (RAL) light gray (7035)

Flammability rating according to UL 94 V0

Housing material Polycarbonate

[Back to topAmbient conditions](#)

Ambient temperature (storage/transport) -40 °C ... 70 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)

Relative humidity (storage/transport) 95 %

[Back to topPCB data](#)

Number of PCB holders 1

PCB thickness 1.8 mm

Mounting position parallel to the DIN rail

Type of PCB mount Latching

[Back to topGeneral information](#)

Type of note Assembly instruction:

Note Refer to the data sheet...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BC 71,6 OT 1010 KMGY MOQ100 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.