

**INDUSTRIAL COMPONENT DATA**

# BC 71,6 OT 2101 KMGY 1016754 PHOENIX CONTACT DIN rail housing for use in distribution boards in accordance w..

Brand: PHOENIX CONTACT | Manufacturer Part Number: BC 71,6 OT 2101 KMGY



|                 |                      |
|-----------------|----------------------|
| Manufacturer    | PHOENIX CONTACT      |
| MPN / Reference | BC 71,6 OT 2101 KMGY |
| Catalog number  | 1016754              |
| Category        | Electronic enclosure |
| Minimum order   | 100 Pcs              |
| Document ID     | EO-0609C0B3F3        |
| Generated       | 2026-08-06           |

## Product Overview

DIN rail housing for use in distribution boards in accordance with DIN 43880, Upper housing part with vents, width: 71.6 mm, height: 89.7 mm, depth: 54.85 mm, color: light gray (7035)

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                |
|--------------|--------------------------------|
| Catalog path | PHOENIX CONTACT > Housing (HS) |
|--------------|--------------------------------|

## Additional Product Information

Key Commercial Data  
 Orderkey 1016754  
 Packing unit 1  
 GTIN 4055626820903  
 Custom tariff number 85389099  
 Item properties  
 Material data  
 PCB data  
 Standards and regulations  
 Dimensions  
 Ambient conditions  
 Packaging information  
 Classifications  
 Item properties

Brief article description Upper part of housing

Type BC 71,6 OT 2101 KMGY

Order No. 1016754

Housing type DIN rail housing for use in distribution boards in accordance with DIN 43880

Housing series BC

Type Upper housing part with vents

Max. IP code to attain IP20

Mounting type Snap in

Connection levels 1 (Both sides)

Ventilation openings present yes

Max. number of positions 44 (pitch: 2.5 mm)

32 (pitch: 3.5 mm)

24 (pitch: 5 mm)

16 (pitch: 7.5 mm)

[Back to top](#)Dimensions

Width [ w ] 71.6 mm

Height [ h ] 89.7 mm

Depth [ d ] 54.85 mm

[Back to top](#)Material data

Color (RAL) light gray (7035)

Flammability rating according to UL 94 V0

Housing material Polycarbonate

[Back to top](#)Ambient conditions

Ambient temperature (storage/transport) -40 °C ... 70 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)

Relative humidity (storage/transport) 95 %

[Back to top](#)PCB data

Number of PCB holders 1

PCB thickness 1.8 mm

Mounting position parallel to the DIN rail

Type of PCB mount Latching

[Back to top](#)Packaging information

Pieces per package 20

Denomination packing units Pcs.

[Back to top](#)Standards and regulations

Flammability rating according to UL 94 V0

[Back to top](#)Classification...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BC 71,6 OT 2101 KMGY with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.