

INDUSTRIAL COMPONENT DATA

BCH-350VF-11 GN 5444165 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: BCH-350VF-11 GN



Manufacturer	PHOENIX CONTACT
MPN / Reference	BCH-350VF-11 GN
Catalog number	5444165
Category	Printed circuit board connector
Minimum order	100 Pcs
Document ID	EO-B79919172C
Generated	2026-08-05

Product Overview

Printed-circuit board connector

Printed circuit board base housing, nominal section: 1.5 mm², color: whitish green, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 11, number of rows: 1, number of poles: 11, number of connections: 11, article family: BCH-VF, pitch: 3.5 mm, mounting: Wave soldering, Pin arrangement: Linear pin arrangement, pin length [P]: 3.4 mm, number of solder pins per potential: 1, plug-in system: BASICLINE 1.5, Plug-in face orientation: Standard, lock: Screw lock, fastening type: Overhead clamping (thread), packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 5444165

Packing unit 100 pc

Minimum order quantity 100 pc

Note Made to Order (non-returnable)

GTIN 4046356835978

Weight per Piece (excluding packing) 3.520 g

Custom tariff number 85366930

Country of origin CN (China)

Dimensions

Length [l] 7.4 mm

Width 48.8 mm

Pitch 3.5 mm

Dimension a 35 mm

Width [w] 48.8 mm

Height [h] 12.6 mm

Height 9.2 mm

Length of the solder pin 3.4 mm

Pin dimensions 0.8 x 0.8 mm

Length 7.4 mm

General

Range of articles BCH-VF

Insulating material group I

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 160 V

Rated voltage (III/2) 160 V

Rated voltage (II/2) 320 V

Connection in acc. with standard EN-VDE

Nominal current I_N 8 A

Maximum load current 8 A

Insulating material PA

Flammability rating according to UL 94 V0

Color pastel green

Number of positions 11

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Flammability rating according to UL 94 V0

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211801UNSPSC 7.090139121432UNSPSC 113912143...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCH-350VF-11 GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.