

INDUSTRIAL COMPONENT DATA

BCH-381H-11 BK 5452036 PHOENIX CONTACT Housing base,nominal Current: 8 A,rated Voltage (III/2): 160 V,N. ° p..

Brand: PHOENIX CONTACT | Manufacturer Part Number: BCH-381H-11 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	BCH-381H-11 BK
Catalog number	5452036
Category	Printed circuit board connector
Minimum order	100 Pcs
Document ID	EO-A016875942
Generated	2026-08-04

Product Overview

Housing base,nominal Current: 8 A,rated Voltage (III/2): 160 V,N. ° poles: 11,Pitch: 3,81 mm,Color: black,contact Surface: Tin,Assembly: wave Soldering

Printed circuit board base case, nominal section: 1.5 mm², color: black, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 11, number of rows: 1, number of poles: 11, number of connections: 11, article family: BCH-H, pitch: 3.81 mm, mounting: Wave soldering, Pin arrangement: Linear pin arrangement, pin length [P]: 3.4 mm, number of solder pins per potential: 1, plug-in system: BASICLINE 1.5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Trade data

Order Code Five million four hundred fifty two thousand thirty six

Packaging unit 100 pcs

Minimum order quantity 100 pcs

Note Manufacturing to the order (no recovery)

GTIN Four trillion forty six billion three hundred fifty six million eight hundred fifty five thousand four hundred fifty seven

Weight per piece (excluding packing) Of 0.003 KGM

Number of the customs tariff Eighty five million three hundred sixty six thousand nine hundred thirty

Country of origin CN (China)

Dimensions

Length [l] 9.2 mm

Width 43.3 mm

Not 3,81 mm

Rated 38.1 mm

Width [w] 43.3 mm

Height [h] 10.8 mm

Mounting height 7.4 mm

Length of the picot 3.4 mm

Dimensions of spikes 0.8 x 0.8 mm

Length 9.2 mm

General

Family articles BCH-H

Group of insulation I

Impulse voltage assigned (III/3) 2.5 kV

Impulse voltage assigned (III/2) 2.5 kV

Impulse voltage assigned to (II/2) 2.5 kV

Reference voltage (III/3) 160 V

Rated voltage (III/2) 160 V

Rated voltage (II/2) 320 V

Connection according to standard EN-VDE

Rated current IN Eight

Insulating material PA

Flammability class according to UL 94 V0

Colours black

Number of poles Eleven

Standards and specifications

Connection according to standard EN-VDE

ASS

Flammability class according to UL 94 V0

Environmental Product Compliance

China RoHS Period of intended use : unlimited = EFUP-e

No hazardous substances exceeding the threshold values ;

Classifications

eCl@ss 4.0272607xxeCl@ss 4.1Twenty seven million two hundred sixty thousand seven hundred oneeCl@ss 5...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCH-381H-11 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.