

INDUSTRIAL COMPONENT DATA

**BCH-381V- 4 GN 5444660 PHOENIX CONTACT Housing
base,nominal Current: 8 A,rated Voltage (III/2): 160 V,N. ° p..**

Brand: PHOENIX CONTACT | Manufacturer Part Number: BCH-381V-4 GN



Manufacturer	PHOENIX CONTACT
MPN / Reference	BCH-381V-4 GN
Catalog number	5444660
Category	Printed circuit board connector
Minimum order	100 Pcs
Document ID	EO-DBBA2C27F3
Generated	2026-08-04

Product Overview

Housing base,nominal Current: 8 A,rated Voltage (III/2): 160 V,N. ° poles: 4,Pitch: 3,81 mm,Color: whitish green,contact Surface: Tin,Assembly: wave Soldering

Printed circuit board base housing, nominal section: 1.5 mm², color: whitish green, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, article family: BCH-V, pitch: 3.81 mm, mounting: Wave soldering, Pin arrangement: Linear pin arrangement, pin length [P]: 3.4 mm, number of solder pins per potential: 1, plug-in system: BASICLINE 1.5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: boxed

PCB headers, nominal current: 8 A, rated voltage (III/2): 160 V, nominal cross section: 1.5 mm², number of positions: 4, pitch: 3.81 mm, color: pastel green, contact surface: Tin, mounting: Wave soldering, pin layout: Linear pinning, solder pin [P]: 3.4 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 5444660

Packing unit 1 pc

Minimum order quantity 100 pc

GTIN 4046356806718

Weight per Piece (excluding packing) 1.058 g

Custom tariff number 85366930

Country of origin CN (China)

Drawings

General

Environmental Product Compliance

Dimensions

Standards and Regulations

Classifications

Drawings

Drilling diagram

Dimensional drawing

Back to topDimensions

Length [l] 7.4 mm

Width 16.63 mm

Pitch 3.81 mm

Dimension a 11.43 mm

Width [w] 16.63 mm

Height [h] 12.6 mm

Height 9.2 mm

Length of the solder pin 3.4 mm

Pin dimensions 0.8 x 0.8 mm

Length 7.4 mm

Back to topGeneral

Range of articles BCH-V

Insulating material group I

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 160 V

Rated voltage (III/2) 160 V

Rated voltage (II/2) 320 V

Connection in acc. with standard EN-VDE

Nominal current I_N 8 A

Insulating material PA

Flammability rating according to UL 94 V0

Color pastel green

Number of positions 4

Back to topStandards and Regulations

Connection in acc. with standard EN-VDE

CUL

Flammability rating according to UL 94 V0

Back to topEnvironmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Back to topClassifications

eCI@ss

eCI@ss 4.0 27260700

eCl@ss 4.1 27260700

eCl@ss 5.0 27260700

eCl@ss 5.1 27260700

eCl@ss 6.0 27260700

eCl@ss 7.0 27440402

eCl@ss 8.0 27440402

eCl@ss 9.0 27440402

[Back to top](#)ETIM

ET...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCH-381V-4 GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.