


INDUSTRIAL COMPONENT DATA

BCH-381VF- 2 GN 5444835 PHOENIX CONTACT Housing base,nominal Current: 8 A,rated Voltage (III/2): 160 V,N. ° ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: BCH-381VF-2 GN



Manufacturer	PHOENIX CONTACT
MPN / Reference	BCH-381VF-2 GN
Catalog number	5444835
Category	Printed circuit board connector
Minimum order	100 Pcs
Document ID	EO-5079C978F8
Generated	2026-08-04

Product Overview

Housing base,nominal Current: 8 A,rated Voltage (III/2): 160 V,N. ° poles: 2,Pitch: 3,81 mm,Color: whitish green,contact Surface: Tin,Assembly: wave Soldering

Printed circuit board base case, nominal section: 1.5 mm², color: whitish green, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, article family: BCH-VF, pitch: 3.81 mm, mounting: Wave soldering, Pin arrangement: Linear pin arrangement, pin length [P]: 3.4 mm, number of solder pins per potential: 1, plug-in system: BASICLINE 1.5, Plug-in face orientation: Standard, lock: Screw lock, fastening type: Overhead clamping (thread), packaging type: boxed PCB base strip, nominal cross-section: 1.5 mm², color: white-green, rated current: 8 A, rated voltage (III/2): 160 V, contact surface: Sn, contact type: pin, number of potentials: 2, number of rows: 1, number of poles: 2, number of connectors: 2, article family: BCH-VF, pitch: 3.81 mm, mounting: wave soldering, pin layout: linear pinning, pin length [P]: 3.4 mm, number of solder pins per potential: 1, connector system: BASICLINE 1.5, orientation mating face: Standard, Locking: Screw locking, Fastening type: Threaded flange, Packing type: packed in carton

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Technical dataItem propertiesProduct Type PCB Floor Strip
Product family BCH-VF
Product Line COMBICON Connectors S
Design Standard

Number of poles 2
Grid dimension 3.81 mm
Number of ports 2
Number of rows 1
Number of potentials 2
Mounting Flange Threaded flange
Pin layout Linear Pinning
Number of solder pins per potential 1
Data maintenance status
Article revision 02
Electrical propertiesNominal current IN 8 A
Rated voltage UN 160 V
Contact resistance 4.3 m?
Rated voltage (III/3) 160 V
Rated Surge Voltage (III/3) 2.5 kV
Rated voltage (III/2) 160 V
Rated Surge Voltage (III/2) 2.5 kV
Rated voltage (II/2) 320 V
Rated Surge Voltage (II/2) 2.5 kV
AssemblyMounting type Wave Soldering
Pin layout Linear Pinning
Flange
Tightening torque 0.3 Nm
Material specificationsMaterial information - Contact
Note WEEE/RoHS compliant, whisker-free according to IEC 60068-2-82/JEDEC JESD 201
Material Contact Cu alloy
Surface finish Electroplated
Metal Surface Contact Area (Top Layer) Tin (4 - 8 um Sn)
Metal Surface Contact Area (Interlayer) Nickel (1.5 - 4 um Ni)
Metal Surface Soldering Area (Top Layer) Tin (4 - 8 um Sn)
Metal Surface Soldering Area (Interlayer) Nickel (1.5 - 4 um Ni)
Material specifications - Housing
Color (Housing) White-green (6019)
Insulating material PA
Insulating material group I
CTI according to IEC 60112 600
Flammability class according to UL 94 V0
Glow wire flammability index GWFI according to EN 60695-2-12 850
Glow wire ignition temperature GWIT according to EN 60695-2-13...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCH-381VF-2 GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.