

INDUSTRIAL COMPONENT DATA

BCH-500H-19 GN 5445193 PHOENIX CONTACT Housing base,nominal Current: 12 A,rated Voltage (III/2): 320 V,N. ° ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: BCH-500H-19 GN



Manufacturer	PHOENIX CONTACT
MPN / Reference	BCH-500H-19 GN
Catalog number	5445193
Category	Printed circuit board connector
Minimum order	100 Pcs
Document ID	EO-AE5F97C5F3
Generated	2026-08-04

Product Overview

Housing base,nominal Current: 12 A,rated Voltage (III/2): 320 V,N. ° poles: 19,Pitch: 5 mm,Color: whitish green,contact Surface: Tin,Assembly: wave Soldering

Printed circuit board base housing, nominal section: 2.5 mm², color: whitish green, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact connection type: Male, number of potentials: 19, number of rows: 1, number of poles: 19, number of connections: 19, article family: BCH-H, pitch: 5 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.5 mm, number of solder pins per potential: 1, plug-in system: BASICLINE 2.5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCH-500H-19 GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.