

INDUSTRIAL COMPONENT DATA

**BCH-500H-3 BK 5452268 PHOENIX CONTACT Housing
base,nominal Current: 12 A,rated Voltage (III/2): 320 V,N. ° p..**

Brand: PHOENIX CONTACT | Manufacturer Part Number: BCH-500H-3 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	BCH-500H-3 BK
Catalog number	5452268
Category	Printed circuit board connector
Minimum order	100 Pcs
Document ID	EO-6F1EFF82CE
Generated	2026-08-05

Product Overview

Housing base,nominal Current: 12 A,rated Voltage (III/2): 320 V,N. ° poles: 3,Pitch: 5 mm,Color: black,contact Surface: Tin,Assembly: wave Soldering

Printed circuit board base housing, nominal section: 2.5 mm², color: black, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact connection type: Male, number of potentials: 3, number of rows: 1, number of poles: 3, number of connections: 3, family of articles: BCH-H, pitch: 5 mm, mounting: Wave soldering, Pin arrangement: Linear pin arrangement, pin length [P]: 3.4 mm, number of solder pins per potential: 1, plug-in system: BASICLINE 2.5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Trade data

Order Code Five million four hundred fifty two thousand two hundred sixty eight

Packaging unit 100 pcs

Minimum order quantity 100 pcs

Note Manufacturing to the order (no recovery)

GTIN Four trillion forty six billion three hundred fifty six million eight hundred fifty three thousand one hundred thirty two

Weight per piece (excluding packing) Of 0.001 KGM

Number of the customs tariff Eighty five million three hundred sixty six thousand nine hundred thirty

Country of origin CN (China)

Dimensions

Length [l] 12 mm

Width 15 mm

Not 5 mm

Rated 10 mm

Width [w] 15 mm

Height [h] 12 mm

Mounting height The 8.6 mm

Length of the picot 3.4 mm

Dimensions of spikes 1 x 1 mm

Length 12 mm

General

Family articles BCH-H

Group of insulation I

Impulse voltage assigned (III/3) 4 kV

Impulse voltage assigned (III/2) 4 kV

Impulse voltage assigned to (II/2) 4 kV

Reference voltage (III/3) 250 V

Rated voltage (III/2) 320 V

Rated voltage (II/2) 400 V

Connection according to standard EN-VDE

Rated current IN Twelve

Maximum charge current Twelve

Insulating material PA

Flammability class according to UL 94 V0

Colours black

Number of poles Three

Standards and specifications

Connection according to standard EN-VDE

ASS

Flammability class according to UL 94 V0

Environmental Product Compliance

China RoHS Period of intended use : unlimited = EFUP-e

No hazardous substances exceeding the threshold values ;

Classifications

eCl@ss 4.0272607xxeCl@ss 4.1Twenty seven million two hundred sixty thousand sev...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCH-500H-3 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.