

## INDUSTRIAL COMPONENT DATA

**BCH-500HF-15 BK 5452364 PHOENIX CONTACT Housing base,nominal Current: 12 A,rated Voltage (III/2): 320 V,N. °..**

Brand: PHOENIX CONTACT | Manufacturer Part Number: BCH-500HF-15 BK



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | PHOENIX CONTACT                 |
| MPN / Reference | BCH-500HF-15 BK                 |
| Catalog number  | 5452364                         |
| Category        | Printed circuit board connector |
| Minimum order   | 100 Pcs                         |
| Document ID     | EO-FCBE6BD49A                   |
| Generated       | 2026-08-03                      |

## Product Overview

Housing base,nominal Current: 12 A,rated Voltage (III/2): 320 V,N. ° poles: 15,Pitch: 5 mm,Color: black,contact Surface: Tin,Assembly: wave Soldering

Printed circuit board base housing, nominal section: 2.5 mm<sup>2</sup>, color: black, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 15, number of rows: 1, number of poles: 15, number of connections: 15, article family: BCH-HF, pitch: 5 mm, mounting: Wave soldering, Pin arrangement: Linear pin arrangement, pin length [P]: 3.5 mm, number of solder pins per potential: 1, plug-in system: BASICLINE 2.5, Plug-in face orientation: Standard, lock: Screw lock, fixing type: Air clamping (thread), packaging type: boxed

PCB headers, nominal cross section: 2.5 mm<sup>2</sup>, color: black, nominal current: 12 A, rated voltage (III/2): 320 V, contact surface: Sn, contact connection type: Pin, number of potentials: 15, number of rows: 1, number of positions: 15, number of connections: 15, product range: BCH-HF, pitch: 5 mm, mounting: Wave soldering, pin layout: Linear pinning, solder pin [P]: 3.23 mm, number of solder pins per potential: 1, plug-in system: BASICLINE 2,5, Pin connector pattern alignment: Standard, locking: Screw locking mechanism, mounting: Threaded flange, type of packaging: packed in cardboard

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                        |
|--------------|----------------------------------------|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |
|--------------|----------------------------------------|

## Additional Product Information

Technical dataProduct propertiesProduct type PCB headers

Product family BCH-HF

Product line COMBICON Connectors M

Type Standard

Number of positions 15  
Pitch 5 mm  
Number of connections 15  
Number of rows 1  
Number of potentials 15  
Mounting flange Threaded flange  
Pin layout Linear pinning  
Solder pins per potential 1  
Data management status  
Article revision 01  
Electrical propertiesNominal current IN 12 A  
Nominal voltage UN 320 V  
Rated voltage (III/3) 250 V  
Rated surge voltage (III/3) 4 kV  
Rated voltage (III/2) 320 V  
Rated surge voltage (III/2) 4 kV  
Rated voltage (II/2) 400 V  
Rated surge voltage (II/2) 4 kV  
MountingMounting type Wave soldering  
Pin layout Linear pinning  
Flange  
Tightening torque 0.3 Nm  
Material specificationsMaterial data - contact  
Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201  
Contact material Cu alloy  
Surface characteristics Tin-plated  
Metal surface contact area (top layer) Tin (4 - 8 µm Sn)  
Metal surface contact area (middle layer) Nickel (1.5 - 4 µm Ni)  
Metal surface soldering area (top layer) Tin (4 - 8 µm Sn)  
Metal surface soldering area (middle layer) Nickel (1.5 - 4 µm Ni)  
Material data - housing  
Color (Housing) black (9005)  
Insulating material PA  
Insulating material group I  
CTI according to IEC 60112 600  
Flammability rating according to UL 94 V0  
Glow wire flammability index GWFI according to EN 60695-2-12 850  
Glow wire ignition temperature GWIT according to EN 60695-2-13 775  
Temperature for the ball pressure test accord...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCH-500HF-15 BK with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.