


INDUSTRIAL COMPONENT DATA

BCH-500V-8 GY 5432562 PHOENIX CONTACT Printed-circuit board connector BCH-500V- 8 GY 5432562

Brand: PHOENIX CONTACT | Manufacturer Part Number: BCH-500V-8 GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	BCH-500V-8 GY
Catalog number	5432562
Category	Printed circuit board connector
Minimum order	100 Pcs
Document ID	EO-8AF454D627
Generated	2026-08-05

Product Overview

Printed-circuit board connector - BCH-500V- 8 GY - 5432562

Printed circuit board base housing, nominal section: 2.5 mm², color: signal gray, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact connection type: Male, number of potentials: 8, number of rows: 1, number of poles: 8, number of connections: 8, article family: BCH-V, pitch: 5 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.4 mm, number of solder pins per potential: 1, plug-in system: BASICLINE 2.5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

PCB headers, nominal current: 12 A, rated voltage (III/2): 320 V, number of positions: 8, pitch: 5 mm, color: signal grey, contact surface: Tin, mounting: Wave soldering

Key Commercial Data

Orderkey 5432562

Packing unit 100 pc

Minimum order quantity 100 pc

Note Made to Order (non-returnable)

GTIN 4046356326537

Weight per Piece (excluding packing) 2.840 g

Custom tariff number 85366930

Country of origin CN (China)

Dimensions

Length [l] 8.6 mm

Width 40 mm

Pitch 5 mm

Dimension a 35 mm

Width [w] 40 mm

Height [h] 15.4 mm

Height 12 mm

Length of the solder pin 3.4 mm

Pin dimensions 1 x 1 mm

Length 8.6 mm

General

Range of articles BCH-V

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 320 V

Rated voltage (II/2) 400 V

Connection in acc. with standard EN-VDE

Nominal current I_N 12 A

Maximum load current 12 A

Insulating material PA

Flammability rating according to UL 94 V0

Color signal grey

Number of positions 8

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0272607xeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss

7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCH-500V-8 GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.