

INDUSTRIAL COMPONENT DATA

BCH-500VS-24 GY 5433231 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: BCH-500VS-24 GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	BCH-500VS-24 GY
Catalog number	5433231
Category	Printed circuit board connector
Minimum order	100 Pcs
Document ID	EO-7D1A47EAEE
Generated	2026-08-04

Product Overview

Printed-circuit board connector

Printed circuit board base housing, nominal section: 2.5 mm², color: signal gray, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 24, number of rows: 1, number of poles: 24, number of connections: 24, family of articles: BCH-VS, pitch: 5 mm, mounting: Wave soldering, Pin arrangement: Linear pin arrangement, pin length [P]: 3.9 mm, number of solder pins per potential: 1, plug-in system: BASICLINE 2.5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 5433231

Packing unit 100 pc

Minimum order quantity 100 pc

Note Made to Order (non-returnable)

GTIN 4046356493529

Weight per Piece (excluding packing) 7.660 g

Custom tariff number 85366930

Country of origin CN (China)

Dimensions

Length [l] 8.6 mm

Width 122 mm

Pitch 5 mm

Dimension a 115 mm

Width [w] 122 mm

Height [h] 15.9 mm

Height 12 mm

Length of the solder pin 3.9 mm

Pin dimensions 1 x 1 mm

Length 8.6 mm

General

Range of articles BCH-VS

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 320 V

Rated voltage (II/2) 400 V

Connection in acc. with standard EN-VDE

Nominal current I_N 12 A

Maximum load current 12 A

Insulating material PA

Flammability rating according to UL 94 V0

Color signal grey

Number of positions 24

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss

7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211801UNSPSC 7.090139121432UNSPSC 1139121432UNSPSC 12.0139121409UNSPSC

13.239121409

ETIM for 5433231 Connectors (EC00263...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCH-500VS-24 GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.