


INDUSTRIAL COMPONENT DATA

BCH-508VF-4 BK 5452494 PHOENIX CONTACT Housing base,nominal Current: 12 A,rated Voltage (III/2): 320 V,N. ° ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: BCH-508VF-4 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	BCH-508VF-4 BK
Catalog number	5452494
Category	Printed circuit board connector
Minimum order	100 Pcs
Document ID	EO-B54471FC1E
Generated	2026-08-05

Product Overview

Housing base,nominal Current: 12 A,rated Voltage (III/2): 320 V,N. ° poles: 4,Pitch: 5,08 mm,Color: black,contact Surface: Tin,Assembly: wave Soldering

Printed circuit board base housing, nominal section: 2.5 mm², color: black, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, family of articles: BCH-VF, pitch: 5.08 mm, mounting: Wave soldering, Pin arrangement: Linear pin arrangement, pin length [P]: 3.9 mm, number of solder pins per potential: 1, plug-in system: BASICLINE 2.5, Plug-in face orientation: Standard, lock: Screw lock, fastening type: Air clamping (thread), packaging type: boxed

PCB headers, nominal cross section: 2.5 mm², color: black, nominal current: 12 A, rated voltage (III/2): 320 V, contact surface: Sn, contact connection type: Pin, number of potentials: 4, number of rows: 1, number of positions: 4, number of connections: 4, product range: BCH-VF, pitch: 5.08 mm, mounting: Wave soldering, pin layout: Linear pinning, solder pin [P]: 3.9 mm, number of solder pins per potential: 1, plug-in system: BASICLINE 2,5, Pin connector pattern alignment: Standard, locking: Screw locking mechanism, mounting: Threaded flange, type of packaging: packed in cardboard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Technical dataProduct propertiesProduct type PCB headers

Product family BCH-VF

Product line COMBICON Connectors M

Type Standard

Number of positions 4
Pitch 5.08 mm
Number of connections 4
Number of rows 1
Number of potentials 4
Mounting flange Threaded flange
Pin layout Linear pinning
Solder pins per potential 1
Data management status
Article revision 02
Electrical propertiesNominal current IN 12 A
Nominal voltage UN 320 V
Contact resistance 2.9 m?
Rated voltage (III/3) 250 V
Rated surge voltage (III/3) 4 kV
Rated voltage (III/2) 320 V
Rated surge voltage (III/2) 4 kV
Rated voltage (II/2) 400 V
Rated surge voltage (II/2) 4 kV
MountingMounting type Wave soldering
Pin layout Linear pinning
Flange
Tightening torque 0.3 Nm
Material specificationsMaterial data - contact
Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201
Contact material Cu alloy
Surface characteristics Tin-plated
Metal surface contact area (top layer) Tin (4 - 8 µm Sn)
Metal surface contact area (middle layer) Nickel (1.5 - 4 µm Ni)
Metal surface soldering area (top layer) Tin (4 - 8 µm Sn)
Metal surface soldering area (middle layer) Nickel (1.5 - 4 µm Ni)
Material data - housing
Color (Housing) black (9005)
Insulating material PA
Insulating material group I
CTI according to IEC 60112 600
Flammability rating according to UL 94 V0
Glow wire flammability index GWFI according to EN 60695-2-12 850
Glow wire ignition temperature GWIT according to EN 60695-2-13 775
Temperature for the...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCH-508VF-4 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.