


INDUSTRIAL COMPONENT DATA

BCH-508VS- 3 GY 2PA 5455332 PHOENIX CONTACT Housing base, nominal Current: 12 A, Color: gray signs, contact ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: BCH-508VS-3 GY 2PA



Manufacturer	PHOENIX CONTACT
MPN / Reference	BCH-508VS-3 GY 2PA
Catalog number	5455332
Category	Printed circuit board connector
Minimum order	100 Pcs
Document ID	EO-A0A6900BAE
Generated	2026-08-06

Product Overview

Housing base, nominal Current: 12 A, Color: gray signs, contact Surface: Tin, Assembly: wave Soldering
Printed circuit board base housing, nominal section: 2.5 mm², color: signal gray, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 2, number of rows: 1, number of poles: 3, number of connections: 2, family of articles: BCH-VS, pitch: 5.08 mm, mounting: Wave soldering, Pin arrangement: Linear pin arrangement, pin length [P]: 3.9 mm, number of solder pins per potential: 1, plug-in system: BASICLINE 2.5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: boxed
PCB headers, nominal cross section: 2.5 mm², color: signal grey, nominal current: 12 A, rated voltage (III/2): 320 V, contact surface: Sn, contact connection type: Pin, number of potentials: 2, number of rows: 1, number of positions: 3, number of connections: 2, product range: BCH-VS, pitch: 5.08 mm, mounting: Wave soldering, pin layout: Linear pinning, solder pin [P]: 3.9 mm, number of solder pins per potential: 1, plug-in system: BASICLINE 2,5, Pin connector pattern alignment: Standard, locking: without, mounting: without, type of packaging: packed in cardboard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Data commercial
Key order Five million four hundred fifty five thousand three hundred thirty two
Packing unit 100 pcs
Key selling AAYBHA -
Minimum order quantity 100 pcs

EAN Four trillion forty six billion three hundred fifty six million nine hundred eighty two thousand sixty one

Unit weight (excluding packaging) 1,050 g

Tariff number tariff Eighty five million three hundred sixty six thousand nine hundred ninety

Country of origin CN (China)

Dimensions

Length [l] 8.57 per mm

Width 17,24 mm

Step 5,08 mm

Average 10,16 mm

Width [w] 17,24 mm

Height [h] 15.9 mm

Height of construction 12 mm

Length of the pin welding 3.9 mm

Dimensions of pin 1 x 1 mm

Length 8.57 per mm

Overview

Family of articles BCH-VS

Tension and sizing (III/3) 250 V

Connection according to standard EN-VDE

Nominal current IN 12 To

Color gray signals

Number of poles Three

Standards and specifications

Connection according to standard EN-VDE

Environmental Product Compliance

China RoHS Space of time for the intended use: unlimited = FEUP-e

No dangerous substances above the thresholds

Ratings

eCl@ss 5.1Twenty seven million two hundred sixty thousand seven hundredeCl@ss 6.0Twenty seven million two hundred sixty thousand seven hundredeCl@ss 7.0Twenty seven million four hundred forty thousand four hundred twoeCl@ss 8.0Twenty seven million four hundred forty thousand four hundred twoeCl@ss 9.0Twenty seven million four hundred forty thousand four hundred two

ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 13....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCH-508VS-3 GY 2PA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.