

INDUSTRIAL COMPONENT DATA

BCP-350- 2 GY BD:15-16 5454171 PHOENIX CONTACT Part plug, nominal Current: 8 A, Technique of connection: Con..

Brand: PHOENIX CONTACT | Manufacturer Part Number: BCP-350- 2 GY BD:15-16



Manufacturer	PHOENIX CONTACT
MPN / Reference	BCP-350- 2 GY BD:15-16
Catalog number	5454171
Category	Cable connector
Minimum order	100 Pcs
Document ID	EO-6C134119A8
Generated	2026-08-05

Product Overview

Part plug, nominal Current: 8 A, Technique of connection: Connection by screw with capsule-traction, Color: gray signs, contact Surface: Tin

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Commercial data
Order key 5454171
Packaging unit 100 pcs
Sell key AAYCAA -
Minimum Order Quantity 100 pcs
Ean 4046356948777
Weight per unit (excluding packaging) 1,500 g
Tariff rate number 85366990
Country of origin CN (China)
Dimensions
Length [l] 16.1 mm
Width [w] 7.7 mm
Height [h] 11.1 mm
Step 3.5 mm

Medium to 3.5 mm

General

Article Family BCP

Number of poles 2

Connection type Screw connection with traction capsule

Sizing voltage (III/3) 160 V

Standard-compliant connection EN-VDE

Nominal Current IN 8 A

Nominal Section 1.5 mm²

Connection data

Rigid conductor section min. 0.2 mm²

Max. rigid conductor section 1.5 mm²

Flexible conductor section min. 0.2 mm²

Max. flexible conductor section 1.5 mm²

Flexible conductor section with toe cap, without min plastic sleeve. 0.25 mm²

Flexible conductor section with toe cap, without plastic sleeve max. 1.5 mm²

Flexible conductor section with tip, with min plastic sleeve. 0.25 mm²

Flexible conductor section with ferrule, with plastic sleeve max. 0.5 mm²

Conductor section AWG min. 24

Conductor section AWG max. 16

2 conductors with the same cross-section, rigid min. 0.2 mm²

2 conductors with the same cross-section, rigid max. 0.5 mm²

2 conductors with the same cross-section, flexible min. 0.25 mm²

2 conductors with the same cross-section, flexible max. 0.75 mm²

2 conductors with the same cross-section, flexible with HAE, without min plastic sleeve. 0.25 mm²

2 conductors with the same cross-section, flexible with HAE without plastic sl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCP-350- 2 GY BD:15-16 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.