


INDUSTRIAL COMPONENT DATA

BCP-350F- 2 BK 5452511 PHOENIX CONTACT Part plug,nominal Current: 8 A,rated Voltage (III/2): 160 V,N. ° pole..

Brand: PHOENIX CONTACT | Manufacturer Part Number: BCP-350F-2 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	BCP-350F-2 BK
Catalog number	5452511
Category	Cable connector
Minimum order	100 Pcs
Document ID	EO-311F04A22B
Generated	2026-08-05

Product Overview

Part plug,nominal Current: 8 A,rated Voltage (III/2): 160 V,N. ° poles: 2,Pitch: 3.5 mm,Technique of connection: Connection by screw with capsule-traction,Color: black,contact Surface: Tin

Connector for printed circuit board, nominal section: 1.5 mm², colour: black, rated current: 8 A, dimensioning voltage (III/2): 160 V, surface contacts: Tin, contact type: Connecting female, Number of potentials: 2, Number of rows: 1, Number of poles per row: 2, number of connections: 2, article family: BCP-F, pitch: 3.5 mm, Connection type: Screw connection with traction capsule, connection direction conductor/printed circuit board: 0°, Stecksystem: BASICLINE 1.5, Lock: Screw lock, packaging type: boxed packaging

PCB connector, nominal cross-section: 1.5 mm², colour: black, rated current: 8 A, dimensioning voltage (III/2): 160 V, contact surface: Sn, contact connection type: Female, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, product series: BCP-F, pitch: 3.5 mm, connection type: screw connection with cage, Screw attachment form: L Longitudinal slot, conductor/board connection direction: 0°, plug system: BASICLINE 1.5, clamping: Screw locking, fixing type: Screw flange, packaging type: packed in carton

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Data commercial

Key order Five million four hundred fifty two thousand five hundred eleven

Packing unit 100 pcs

Key selling AAYCAA -

Minimum order quantity 100 pcs

EAN Four trillion forty six billion three hundred fifty six million eight hundred fifty thousand seven hundred four

Unit weight (excluding packaging) 2,236 g

Tariff number tariff Eighty five million three hundred sixty six thousand nine hundred ninety

Country of origin CN (China)

Dimensions

Length [l] 16,1 mm

Width [w] 17,3 mm

Height [h] 11,1 mm

Step 3.5 mm

Average 3.5 mm

Overview

Family of articles BCP-F

Number of poles Two

Type of connection Connection by screw with capsule-traction

Group insulating material I

Transient voltage design (III/3) 2.5 kV

Transient voltage design (III/2) 2.5 kV

Transient voltage design (II/2) 2.5 kV

Tension and sizing (III/3) 160 V

Tension and sizing (III/2) 160 V

Tension and sizing (II/2) 320 V

Connection according to standard EN-VDE

Nominal current IN 8 To

Nominal cross section 1.5 mm²

Maximum load current 8 A (with a section of conductor 1.5 mm²)

Isolation PA

Class of flammability according to UL 94 V0

Gauge male A1

Length desaislar 7 mm

Screw thread M2

Tightening torque min. 0.22 Nm

Tightening torque max. 0,25 Nm

Data connection

Core cross-section rigid min. 0,2 mm²

Section of conductor rigid max. 1.5 mm²

Section of flexible conductor, min. 0,2 mm²

Section of flexible conductor max. 1.5 mm²

Section of flexible conductor with toe cap, without plastic sleeve min. 0.25 mm²

Sect...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCP-350F-2 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.