


## INDUSTRIAL COMPONENT DATA

# BCP-381- 2 GY 5434926 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: BCP-381-2 GY



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | PHOENIX CONTACT |
| MPN / Reference | BCP-381-2 GY    |
| Catalog number  | 5434926         |
| Category        | Cable connector |
| Minimum order   | 100 Pcs         |
| Document ID     | EO-E54D35FE44   |
| Generated       | 2026-08-04      |

## Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal cross-section: 1.5 mm<sup>2</sup>, color: signal gray, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Female, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, article family: BCP, pitch: 3.81 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, conductor/printed circuit board connection direction: 0 °, plug-in system:

BASICLINE 1.5, lock: without, fixing type: without, packaging type: boxed

PCB connector, nominal cross-section: 1.5 mm<sup>2</sup>, colour: signal grey, rated current: 8 A, dimensioning voltage (III/2): 160 V, contact surface: Sn, contact connection type: Female, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, product series: BCP, pitch: 3.81 mm, connection type: Screw connection with cage, screw attachment form: L Longitudinal slot, conductor/board connection direction: 0 °, plug system: BASICLINE 1.5, clamping: none, fastening type: none, packaging type: packed in carton

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

## Additional Product Information

Key Commercial Data

Orderkey 5434926

Packing unit 100 pc

Minimum order quantity 100 pc

GTIN 4046356171748

Weight per Piece (excluding packing) 1.000 g

Custom tariff number 85366990

Country of origin CN (China)

Dimensions

Length [ l ] 16.1 mm

Width [ w ] 8.41 mm

Height [ h ] 11.1 mm

Pitch 3.81 mm

Dimension a 3.81 mm

General

Range of articles BCP

Number of positions 2

Connection method Screw connection with tension sleeve

Insulating material group I

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 160 V

Rated voltage (III/2) 160 V

Rated voltage (II/2) 320 V

Connection in acc. with standard EN-VDE

Nominal current IN 8 A

Nominal cross section 1.5 mm<sup>2</sup>

Maximum load current 8 A (with 1.5 mm<sup>2</sup> conductor cross section)

Insulating material PA

Flammability rating according to UL 94 V0

Internal cylindrical gage A1

Stripping length 7 mm

Screw thread M2

Tightening torque, min 0.22 Nm

Tightening torque max 0.25 Nm

Connection data

Conductor cross section solid min. 0.2 mm<sup>2</sup>

Conductor cross section solid max. 1.5 mm<sup>2</sup>

Conductor cross section flexible min. 0.2 mm<sup>2</sup>

Conductor cross section flexible max. 1.5 mm<sup>2</sup>

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm<sup>2</sup>

Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm<sup>2</sup>

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm<sup>2</sup>

Conductor cross section flexible, with ferrule with plastic sleeve m...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCP-381-2 GY with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.