

INDUSTRIAL COMPONENT DATA

BCP-381F-14 GY 5435239 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: BCP-381F-14 GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	BCP-381F-14 GY
Catalog number	5435239
Category	Cable connector
Minimum order	100 Pcs
Document ID	EO-D54A337662
Generated	2026-08-06

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 1.5 mm², color: signal grey, rated current: 8 A, sizing voltage (III/2): 160 V, surface contacts: Tin, contact type: Connection female, Number of potentials: 14, Number of rows: 1, Number of poles per row: 14, number of connections: 14, article family: BCP-F, step: 3.81 mm, connection type: Screw connection with traction capsule, connection direction conductor/printed circuit board: 0 °, Stecksystem: BASICLINE 1.5, Lock: Locking by screw, type of packaging: boxed packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

PCB connector, nominal current: 8 A, rated voltage (III/2): 160 V, number of positions: 14, pitch: 3.81 mm, connection method: Screw connection with tension sleeve, color: signal grey, contact surface: Tin

Key Commercial Data

Orderkey 5435239

Packing unit 100 pc

Minimum order quantity 100 pc

Note Made to Order (non-returnable)

GTIN 4046356172059

Weight per Piece (excluding packing) 11.260 g

Custom tariff number 85366990

Country of origin CN (China)

Dimensions

Length [l] 16.1 mm

Width [w] 63.73 mm

Height [h] 11.1 mm

Pitch 3.81 mm

Dimension a 49.53 mm

General

Range of articles BCP-F

Number of positions 14

Connection method Screw connection with tension sleeve

Insulating material group I

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 160 V

Rated voltage (III/2) 160 V

Rated voltage (II/2) 320 V

Connection in acc. with standard EN-VDE

Nominal current IN 8 A

Nominal cross section 1.5 mm²

Maximum load current 8 A (with 1.5 mm² conductor cross section)

Insulating material PA

Flammability rating according to UL 94 V0

Internal cylindrical gage A1

Stripping length 7 mm

Screw thread M2

Tightening torque, min 0.22 Nm

Tightening torque max 0.25 Nm

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 1.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 1.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCP-381F-14 GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.