

INDUSTRIAL COMPONENT DATA

BCP-500-14 GN BDWH-10SO VPE250 5430279 PHOENIX CONTACT Printed-circuit board connector BCP-500-14 GN BDWH-10..

Brand: PHOENIX CONTACT | Manufacturer Part Number: BCP-500-14 GN BDWH-10SO VPE250



Manufacturer	PHOENIX CONTACT
MPN / Reference	BCP-500-14 GN BDWH-10SO VPE250
Catalog number	5430279
Category	Cable connector
Minimum order	250 Pcs
Document ID	EO-CD8ECBF94B
Generated	2026-08-05

Product Overview

Printed-circuit board connector - BCP-500-14 GN BDWH-10SO VPE250 - 5430279

Connector for printed circuit board, nominal cross-section: 2.5 mm², color: off-white, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 14, number of rows: 1, number of poles: 14, number of connections: 14, article family: BCP, pitch: 5 mm, connection type: Screw connection with traction capsule, connection direction conductor/printed circuit board: 0 °, clamping hook: - Clamping hook, plug-in system: BASICLINE 2.5, locking: without, fixing type: without, packaging type: packed in box

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

PCB connector, nominal current: 12 A, rated voltage (III/2): 320 V, number of positions: 14, pitch: 5 mm, connection method: Screw connection with tension sleeve, color: pastel green, contact surface: Tin

Key Commercial Data

Orderkey 5430279

Packing unit 250 pc

Minimum order quantity 250 pc

Note Made to Order (non-returnable)

GTIN 4055626340968

Weight per Piece (excluding packing) 22.950 g

Custom tariff number 85366990

Country of origin CN (China)

Dimensions

Length [l] 18.2 mm

Width [w] 70 mm

Height [h] 15 mm

Pitch 5 mm

Dimension a 65 mm

General

Range of articles BCP

Number of positions 14

Connection method Screw connection with tension sleeve

Insulating material group I

Rated voltage (III/2) 320 V

Nominal current IN 12 A

Nominal cross section 2.5 mm²

Flammability rating according to UL 94 V0

Screw thread M3

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

REACH SVHC

Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440309eCl@ss 8.027440309eCl@ss 9.027440309

ETIM 5.0EC002638ETIM 6.0EC002638ETIM 7.0EC002638

ETIM for 5430279 Connectors (EC002638)

Feature Name

Feature Value

Type of connection (EF000064)

Other

Contact type (EF001587)

Bus

Number of poles (EF001391)

14

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF007326...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCP-500-14 GN BDWH-10SO VPE250 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.