

INDUSTRIAL COMPONENT DATA

BCP-500-24 BK 5452234 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: BCP-500-24 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	BCP-500-24 BK
Catalog number	5452234
Category	Cable connector
Minimum order	100 Pcs
Document ID	EO-D3E150B644
Generated	2026-08-04

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 2.5 mm², color: black, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 24, number of rows: 1, number of poles: 24, number of connections: 24, article family: BCP, pitch: 5 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, conductor/printed circuit board connection direction: 0 °, clamping hook: - Clamping hook, plug-in system: BASICLINE 2.5, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Key Commercial Data

Orderkey 5452234

Packing unit 100 pc

Minimum order quantity 100 pc

Note Made to Order (non-returnable)

GTIN 4046356853477

Weight per Piece (excluding packing) 39.450 g

Custom tariff number 85366990

Country of origin CN (China)

Dimensions

Length [l] 18.2 mm
Width [w] 120 mm
Height [h] 15 mm
Pitch 5 mm
Dimension a 115 mm
General
Range of articles BCP
Number of positions 24
Connection method Screw connection with tension sleeve
Insulating material group I
Rated surge voltage (III/3) 4 kV
Rated surge voltage (III/2) 4 kV
Rated surge voltage (II/2) 4 kV
Rated voltage (III/3) 250 V
Rated voltage (III/2) 320 V
Rated voltage (II/2) 630 V
Connection in acc. with standard EN-VDE
Nominal current I_N 12 A
Nominal cross section 2.5 mm²
Maximum load current 12 A (with a 2.5 mm² conductor cross section)
Insulating material PA
Flammability rating according to UL 94 V0
Stripping length 7 mm
Screw thread M3
Tightening torque, min 0.4 Nm
Tightening torque max 0.5 Nm
Connection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 2.5 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 2.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCP-500-24 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.