

INDUSTRIAL COMPONENT DATA

BCP-500F-20 GY 5435718 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: BCP-500F-20 GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	BCP-500F-20 GY
Catalog number	5435718
Category	Cable connector
Minimum order	100 Pcs
Document ID	EO-0C9D99DBB7
Generated	2026-08-03

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 2.5 mm², color: signal gray, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 20, number of rows: 1, number of poles: 20, number of connections: 20, article family: BCP-F, pitch: 5 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, conductor connection direction/printed circuit board: 0 °, clamping hook: - without clamping hook, plug-in system: BASICLINE 2.5, locking: Screw locking, fixing type: Air clamping (screw), packaging type: boxed

PCB connector, nominal current: 12 A, rated voltage (III/2): 320 V, nominal cross section: 2.5 mm², number of positions: 20, pitch: 5 mm, connection method: Screw connection with tension sleeve, color: signal grey, contact surface: Tin

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 5435718

Packing unit 1 pc

Minimum order quantity 100 pc

GTIN 4046356494328

Weight per Piece (excluding packing) 0.000 g

Custom tariff number 85366990

Country of origin CN (China)

Drawings

General

Standards and Regulations

Classifications

Dimensions

Connection data

Environmental Product Compliance

Drawings

Diagram

Dimensional drawing

[Back to top](#)Dimensions

Length [l] 18.2 mm

Width [w] 109.94 mm

Height [h] 15 mm

Pitch 5 mm

Dimension a 95 mm

[Back to top](#)General

Range of articles BCP-F

Number of positions 20

Connection method Screw connection with tension sleeve

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 320 V

Rated voltage (II/2) 630 V

Nominal current I_N 12 A

Nominal cross section 2.5 mm²

Maximum load current 12 A (with a 2.5 mm² conductor cross section)

Insulating material PA

Flammability rating according to UL 94 V0

Stripping length 7 mm

Screw thread M3

Tightening torque, min 0.4 Nm

Tightening torque max 0.5 Nm

[Back to top](#)Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 2.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²

Conductor cross section flexible, wit...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCP-500F-20 GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.