

INDUSTRIAL COMPONENT DATA

BCP-508-17 GN 5448734 PHOENIX CONTACT Part plug,nominal Current: 12 A, rated Voltage (III/2): 320 V,N. ° pole..

Brand: PHOENIX CONTACT | Manufacturer Part Number: BCP-508-17 GN



Manufacturer	PHOENIX CONTACT
MPN / Reference	BCP-508-17 GN
Catalog number	5448734
Category	Cable connector
Minimum order	100 Pcs
Document ID	EO-C9C047845E
Generated	2026-08-05

Product Overview

Part plug,nominal Current: 12 A, rated Voltage (III/2): 320 V,N. ° poles: 17, Pitch: 5,08 mm, the Technique of connection: Connection by screw with capsule-traction, Color: whitish green, contact Surface: Tin
Connector for printed circuit board, nominal cross-section: 2.5 mm², color: off-white, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 17, number of rows: 1, number of poles: 17, number of connections: 17, article family: BCP, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping method: H1L Philipps-Recess with longitudinal groove, conductor connection direction/printed circuit board: 0 °, clamping hook: - Clamping hook, plug-in system: BASICLINE 2.5, locking: without, fixing type: without, packaging type: packed in box

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Commercial data
Order key 5448734
Packaging unit 100 pcs
Sell key AAYBAA -
Minimum Order Quantity 100 pcs
Ean 4046356829106

Weight per unit (excluding packaging) 28,153 g

Tariff rate number 85366990

Country of origin CN (China)

Dimensions

Length [l] 18.2 mm

Width [w] 86.36 mm

Height [h] 15 mm

Step 5.08 mm

Medium to 81.28 mm

General

Article Family BCP

Number of poles 17

Connection type Screw connection with traction capsule

Insulating material group I

Dimensioning transient voltage (III/3) 4 kV

Dimensioning Transient Voltage (III/2) 4 kV

Dimensioning transient voltage (II/2) 4 kV

Dimensioning voltage (III/2) 320 V

Sizing voltage (II/2) 630 V

Standard-compliant connection EN-VDE

Nominal Current IN 12 A

Nominal Section 2.5 mm²

Maximum Charging Current 12 A (with a conductor cross-section of 2.5 mm²)

Isolation PA

Combustibility class according to UL 94 V0

Length to be de-insulated 7 mm

Min. tightening torque. 0.4 Nm

Max. tightening torque. 0.5 Nm

Connection data

Rigid conductor section min. 0.2 mm²

Max. rigid conductor section 2.5 mm²

Flexible conductor section min. 0.2 mm²

Max. flexible conductor section 2.5 mm²

Flexible conductor section with toe cap, without min plastic sleeve. 0.25 mm²

Flexible conductor section with toe cap, without plastic sleeve max. 2.5 mm²

Flexible conductor section with tip, with min plastic sleeve. 0.25 mm²

Flexible conductor section with ferrule, with plastic sleeve max. 2.5 mm²

Conductor section AWG min. 24

Conductor section AWG max. 12

2 cond...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCP-508-17 GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.