

INDUSTRIAL COMPONENT DATA

BCP-508- 2 BK BDWH:1-2 5454359 PHOENIX CONTACT Part plug, nominal Current: 12 A, Technique of connection: Co..

Brand: PHOENIX CONTACT | Manufacturer Part Number: BCP-508- 2 BK BDWH:1-2



Manufacturer	PHOENIX CONTACT
MPN / Reference	BCP-508- 2 BK BDWH:1-2
Catalog number	5454359
Category	Cable connector
Minimum order	100 Pcs
Document ID	EO-3FEB4C7378
Generated	2026-08-05

Product Overview

Part plug, nominal Current: 12 A, Technique of connection: Connection by screw with capsule-traction, Color: black, contact Surface: Tin

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Data commercial

Key order Five million four hundred fifty four thousand three hundred fifty nine

Packing unit 100 pcs

Key selling AAYBAA -

Minimum order quantity 500 pcs

EAN Four trillion forty six billion three hundred fifty six million nine hundred ninety nine thousand seven hundred eighty six

Unit weight (excluding packaging) 3,000 g

Tariff number tariff Eighty five million three hundred sixty six thousand nine hundred ninety

Country of origin CN (China)

Dimensions

Length [l] 18,2 mm

Width [w] 10,16 mm

Height [h] 15 mm

Step 5,08 mm

Average 5,08 mm

Overview

Family of articles BCP

Number of poles Two

Type of connection Connection by screw with capsule-traction

Connection according to standard EN-VDE

Nominal current IN 12 To

Nominal cross section 2.5 mm²

Data connection

Core cross-section rigid min. 0,2 mm²

Section of conductor rigid max. 2.5 mm²

Section of flexible conductor, min. 0,2 mm²

Section of flexible conductor max. 2.5 mm²

Section of flexible conductor with toe cap, without plastic sleeve min. 0.25 mm²

Section of flexible conductor with toe cap, without plastic sleeve max. 2.5 mm²

Section of flexible conductor with toe, with plastic sleeve min. 0.25 mm²

Section of flexible conductor with toe, with plastic sleeve max. 2.5 mm²

Section of conductor AWG min. Twenty four

Section of conductor AWG max. Twelve

2 conductors with same cross section, rigid min. 0,2 mm²

2 conductors with same cross section, rigid max. 1 mm²

2 conductors with same cross section, flexible,....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCP-508- 2 BK BDWH:1-2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.