

INDUSTRIAL COMPONENT DATA

BCP-508-20 BK 5452251 PHOENIX CONTACT Part plug,nominal Current: 12 A,rated Voltage (III/2): 320 V,N. ° pole..

Brand: PHOENIX CONTACT | Manufacturer Part Number: BCP-508-20 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	BCP-508-20 BK
Catalog number	5452251
Category	Cable connector
Minimum order	100 Pcs
Document ID	EO-7B5D404ED4
Generated	2026-08-06

Product Overview

Part plug,nominal Current: 12 A,rated Voltage (III/2): 320 V,N. ° poles: 20,Pitch: 5,08 mm,the Technique of connection: Connection by screw with capsule-traction,Color: black,contact Surface: Tin
Connector for printed circuit board, nominal section: 2.5 mm², color: black, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 20, number of rows: 1, number of poles: 20, number of connections: 20, article family: BCP, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping form: H1L Philipps-Recess with longitudinal groove, connection direction conductor/printed circuit board: 0 °, clamping hook: - Clamping hook, plug-in system: BASICLINE 2.5, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Data commercial

Key order Five million four hundred fifty two thousand two hundred fifty one

Packing unit 100 pcs

Key selling AAYBAA -

Minimum order quantity 100 pcs

EAN Four trillion forty six billion three hundred fifty six million eight hundred fifty three thousand three hundred nine

Unit weight (excluding packaging) 33,512 g

Tariff number tariff Eighty five million three hundred sixty six thousand nine hundred ninety

Country of origin CN (China)

Dimensions

Length [l] 18,2 mm

Width [w] 101.6 mm

Height [h] 15 mm

Step 5,08 mm

Average 96,52 mm

Overview

Family of articles BCP

Number of poles Twenty

Type of connection Connection by screw with capsule-traction

Group insulating material I

Transient voltage design (III/3) 4 kV

Transient voltage design (III/2) 4 kV

Transient voltage design (II/2) 4 kV

Tension and sizing (III/2) 320 V

Tension and sizing (II/2) 630 V

Connection according to standard EN-VDE

Nominal current IN 12 To

Nominal cross section 2.5 mm²

Maximum load current 12 (with a section of conductor 2.5 mm²)

Isolation PA

Class of flammability according to UL 94 V0

Length desaislar 7 mm

Tightening torque min. 0.4 Nm

Tightening torque max. 0.5 Nm

Data connection

Core cross-section rigid min. 0,2 mm²

Section of conductor rigid max. 2.5 mm²

Section of flexible conductor, min. 0,2 mm²

Section of flexible conductor max. 2.5 mm²

Section of flexible conductor with toe cap, without plastic sleeve min. 0.25 mm²

Section of flexible conductor with toe cap, without plastic sle...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCP-508-20 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.