

INDUSTRIAL COMPONENT DATA

BCP-508- 3 GN BD:-,I8 1088022 PHOENIX CONTACT

Connector for printed circuit board, nominal current: 12 A, nu..

Brand: PHOENIX CONTACT | Manufacturer Part Number: BCP-508-3 GN BD:-,I8



Manufacturer	PHOENIX CONTACT
MPN / Reference	BCP-508-3 GN BD:-,I8
Catalog number	1088022
Category	Cable connector
Minimum order	2000 Pcs
Document ID	EO-B962EAE0A4
Generated	2026-08-03

Product Overview

Connector for printed circuit board, nominal current: 12 A, number of poles: 3, pitch: 5,08 mm, type of Connection:

Connection by screw with capsule-traction, color: whitish green, surface contacts: Tin

Connector for printed circuit board, nominal section: 2.5 mm², color: off-white green, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 3, number of rows: 1, number of poles: 3, number of connections: 3, article family: BCP, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping method: H1L Philipps-Recess with longitudinal groove, conductor connection direction/printed circuit board: 0 °, clamping hook: - Clamping hook, plug-in system: BASICLINE 2.5, locking: without, fixing type: without, packaging type: packed in box

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Technical dataItem PropertiesProduct Type Printed Circuit Board Connector

Product Family BCP

Product Line COMBICON Connectors M

Number of poles 3

Step 5.08 mm

Number of connections 3

Number of rows 1
Number of potentials 3
Data Maintenance Status
Article Review 01
Electrical PropertiesNominal Current IN 12 A
Nominal voltage UN 320 V
Contact resistance 2.1 mΩ
Sizing voltage (III/3) 250 V
Dimensioning transient voltage (III/3) 4 kV
Dimensioning voltage (III/2) 320 V
Dimensioning Transient Voltage (III/2) 4 kV
Nominal voltage (II/2) 630 V
Dimensioning transient voltage (II/2) 4 kV
Connection dataConnection technology
Construction Standard
Connector System BASICLINE 2.5
Nominal Section 2.5 mm²
Contact Connection Type Female
Blockade
Locking system without
Clamping flange without
Connecting Conductors
Connection type Screw connection with traction capsule
Connection Direction Driver/PCB 0 °
Rigid conductor section 0.2 mm² ... 2.5 mm²
Flexible conductor section 0.2 mm² ... 2.5 mm²
AWG Conductor Section 24 ... 12
Flexible conductor section with toe cap, without plastic sleeve 0.25 mm² ... 2.5 mm²
Flexible conductor section with toe cap, with plastic sleeve 0.25 mm² ... 2.5 mm²
2 conductors with the same cross-section, rigid 0.2 mm² ... 1 mm²
2 conductors with the same cross-section, flexible 0.2 mm² ... 1.5 mm²
2 conductors of equal cross-section, flexible with toe cap, without plastic sleeve 0.25 mm² ... 1 mm²
2 conductors with the same cross-section, flexible with TWIN toe cap wi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCP-508-3 GN BD:-,I8 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.