

INDUSTRIAL COMPONENT DATA

BCP-508- 3 GY BD:Y-24 5455714 PHOENIX CONTACT PCB connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: BCP-508- 3 GY BD:Y-24



Manufacturer	PHOENIX CONTACT
MPN / Reference	BCP-508- 3 GY BD:Y-24
Catalog number	5455714
Category	Cable connector
Minimum order	100 Pcs
Document ID	EO-B379115821
Generated	2026-08-05

Product Overview

PCB connector

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 5455714
Packing unit 100 pc
Minimum order quantity 100 pc
Note Made to Order (non-returnable)
GTIN 4055626019703
Weight per Piece (excluding packing) 4.000 g
Custom tariff number 85366990
Country of origin CN (China)
Dimensions
Length [l] 18.2 mm
Width [w] 15.24 mm
Height [h] 15 mm
Pitch 5.08 mm
Dimension a 10.16 mm

General

Range of articles BCP

Number of positions 3

Connection method Screw connection with tension sleeve

Connection in acc. with standard EN-VDE

Nominal current IN 12 A

Nominal cross section 2.5 mm²**Connection data**Conductor cross section solid min. 0.2 mm²Conductor cross section solid max. 2.5 mm²Conductor cross section flexible min. 0.2 mm²Conductor cross section flexible max. 2.5 mm²Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

2 conductors with same cross section, solid min. 0.2 mm²2 conductors with same cross section, solid max. 1 mm²2 conductors with same cross section, stranded min. 0.2 mm²2 conductors with same cross section, stranded max. 1.5 mm²2 conductors with same cross section, stranded, ferrules without plastic sleeve, min. 0.25 mm²

2 conductors with same c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCP-508- 3 GY BD:Y-24 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.