

INDUSTRIAL COMPONENT DATA

BCP-508- 9 BK 5452240 PHOENIX CONTACT Part plug,nominal Current: 12 A,rated Voltage (III/2): 320 V,N. ° pole..

Brand: PHOENIX CONTACT | Manufacturer Part Number: BCP-508-9 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	BCP-508-9 BK
Catalog number	5452240
Category	Cable connector
Minimum order	100 Pcs
Document ID	EO-360080CA7E
Generated	2026-08-05

Product Overview

Part plug,nominal Current: 12 A,rated Voltage (III/2): 320 V,N. ° poles: 9,Pitch: 5,08 mm,the Technique of connection: Connection by screw with capsule-traction,Color: black,contact Surface: Tin
Connector for printed circuit board, nominal section: 2.5 mm², color: black, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 9, number of rows: 1, number of poles: 9, number of connections: 9, article family: BCP, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping form: H1L Philipps-Recess with longitudinal groove, connection direction conductor/printed circuit board: 0 °, clamping hook: - Clamping hook, plug-in system: BASICLINE 2.5, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Trade data

Order Code Five million four hundred fifty two thousand two hundred forty

Packaging unit 100 pcs

Minimum order quantity 100 pcs

Note Manufacturing to the order (no recovery)

GTIN Four trillion forty six billion three hundred fifty six million eight hundred fifty three thousand four hundred fifteen

Weight per piece (excluding packing) Of 0.014 KGM

Number of the customs tariff Eighty five million three hundred sixty six thousand nine hundred ninety

Country of origin CN (China)

Dimensions

Length [l] 18,2 mm

Width [w] A 45.72 mm

Height [h] 15 mm

Not 5.08 mm

Rated 40,64 mm

General

Family articles BCP

Number of poles Nine

Type of connection Screw with ring

Group of insulation I

Impulse voltage assigned (III/3) 4 kV

Impulse voltage assigned (III/2) 4 kV

Impulse voltage assigned to (II/2) 4 kV

Rated voltage (III/2) 320 V

Rated voltage (II/2) 630 V

Connection according to standard EN-VDE

Rated current IN Twelve

Nominal Section 2.5 mm²

Maximum charge current 12 A (for wire cross-section 2.5 mm²)

Insulating material PA

Flammability class according to UL 94 V0

Length stripping tool 7 mm

Tightening torque min. 0.4 Nm

Tightening torque max. 0.5 Nm

Characteristics of connection

Wire cross-Section, rigid min. 0,2 mm²

Wire cross-Section rigid max. 2.5 mm²

Wire cross-Section flexible min. 0,2 mm²

Wire cross-Section flexible max. 2.5 mm²

Wire cross-Section flexible with wire-end sleeve without inlet cone insulation max. 0.25 mm²

2.5 mm²

Wire cross-Section flexible with ferrule...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCP-508-9 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.