

INDUSTRIAL COMPONENT DATA

BCP-508F-11 GY 5436047 PHOENIX CONTACT Printed-circuit board connector BCP-508F-11 GY 5436047

Brand: PHOENIX CONTACT | Manufacturer Part Number: BCP-508F-11 GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	BCP-508F-11 GY
Catalog number	5436047
Category	Cable connector
Minimum order	100 Pcs
Document ID	EO-DCBED4D093
Generated	2026-08-03

Product Overview

Printed-circuit board connector - BCP-508F-11 GY - 5436047

Connector for printed circuit board, nominal section: 2.5 mm², color: gray signals, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 11, number of rows: 1, number of poles: 11, number of connections: 11, article family: BCP-F, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping method: H1L Philipps-Recess with longitudinal groove, connection direction conductor/printed circuit board: 0 °, clamping hook: - without clamping hook, plug-in system: BASICLINE 2.5, locking: Screw locking, fixing type: Aerial clamping (screw), packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

PCB connector, nominal current: 12 A, rated voltage (III/2): 320 V, number of positions: 11, pitch: 5.08 mm, connection method: Screw connection with tension sleeve, color: signal grey, contact surface: Tin

Key Commercial Data

Orderkey 5436047

Packing unit 100 pc

Minimum order quantity 100 pc

Note Made to Order (non-returnable)

GTIN 4046356172448

Weight per Piece (excluding packing) 19.890 g

Custom tariff number 85366990

Country of origin CN (China)

Dimensions

Length [l] 18.2 mm

Width [w] 65.9 mm

Height [h] 15 mm

Pitch 5.08 mm

Dimension a 50.8 mm

General

Range of articles BCP-F

Number of positions 11

Connection method Screw connection with tension sleeve

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/2) 320 V

Rated voltage (II/2) 630 V

Nominal current I_N 12 A

Nominal cross section 2.5 mm²

Maximum load current 12 A (with a 2.5 mm² conductor cross section)

Insulating material PA

Flammability rating according to UL 94 V0

Stripping length 7 mm

Screw thread M3

Tightening torque, min 0.4 Nm

Tightening torque max 0.5 Nm

Connection data

Minimum AWG according to UL/CUL 30

Maximum AWG according to UL/CUL 12

Standards and Regulations

Connection in acc. with standard CUL

Flammability rating according to UL 94 V0

Environmental Product Compliance

REACH SVHC

Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Ca...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCP-508F-11 GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.