

INDUSTRIAL COMPONENT DATA

BCVP-508R- 5 GY 5438207 PHOENIX CONTACT Part plug,nominal Current: 12 A,rated Voltage (III/2): 320 V,N. ° po..

Brand: PHOENIX CONTACT | Manufacturer Part Number: BCVP-508R- 5 GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	BCVP-508R- 5 GY
Catalog number	5438207
Category	Cable connector
Minimum order	100 Pcs
Document ID	EO-8FAC507A93
Generated	2026-08-03

Product Overview

Part plug,nominal Current: 12 A,rated Voltage (III/2): 320 V,N. ° poles: 5,Pitch: 5,08 mm,the Technique of connection: Connection by screw with capsule-traction,Color: gray signs,contact Surface: Tin

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Commercial data

Ordering code 5438207

Pieces/pack 50 PCS

Sales key AAYBAA -

Minimum order quantity 100 PCS

GTIN 4046356469166

Weight per piece (excluding packaging) 10,623 g

Customs Tariff number 85366990

Country of origin DE (Germany)

dimensions

Length [L] 12.52 mm

Width [W] 25.6 mm

Height [h] 26.03 mm

Step 5.08 mm

Measure A 20.32 mm
generality
Article family BCPV-R
No. of poles 5
Link Screw connection with cage
Insulation Material Group The
Sizing impulse voltage (III/3) 4 kV
Sizing Impulse Voltage (III/2) 4 kV
Sizing Impulse Voltage (II/2) 4 kV
Sizing voltage (III/3) 250 V
Sizing voltage (III/2) 320 V
Sizing voltage (II/2) 630 V
Rated Current IN 12 A
Nominal cross-section 2.5 mm²
Maximum load current 12 A (with a conductor cross-section of 2.5 mm²)
Insulation material PA
Combustibility class according to UL 94 V0
Stripping length 7 mm
Thread M3
Torque min. 0.5 Nm
Max. torque 0.6 Nm
Connection data
Rigid conductor cross-section min. 0.2 mm²
Solid conductor cross-section max. 2.5 mm²
Flexible conductor cross-section min. 0.2 mm²
Flexible conductor cross-section max. 2.5 mm²
Flexible conductor cross-section with cable lug without plastic collar min. 0.25 mm²
Flexible conductor cross-section with cable lug without plastic collar max. 2.5 mm²
Flexible conductor cross-section with cable lug with plastic collar min. 0.25 mm²
Flexible conductor cross-section with cable lug with plastic collar max. 2.5 mm²
Conductor cross-section AWG min. 24
Conductor cross-section AWG max. 12
2 c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCPV-508R- 5 GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.