

INDUSTRIAL COMPONENT DATA

BCW-500X10-13 GN 1304189 PHOENIX CONTACT Printed circuit board terminal, rated current: 15 A, nominal cross-..

Brand: PHOENIX CONTACT | Manufacturer Part Number: BCW-500X10-13 GN



Manufacturer	PHOENIX CONTACT
MPN / Reference	BCW-500X10-13 GN
Catalog number	1304189
Category	Printed circuit board terminal
Minimum order	1000 Pcs
Document ID	EO-1BFB506252
Generated	2026-08-05

Product Overview

Printed circuit board terminal, rated current: 15 A, nominal cross-section: 2.5 mm², number of potentials: 13, number of rows: 1, number of poles per row: 13, article family: BCW-X10, pitch: 5 mm, connection type: Screw connection with wire protection bracket, screw clamping form: H1L Philipps-Recess with longitudinal groove, Mounting: Wave Soldering, Conductor/PCB Connection Direction: 0°, Color: Whitish Green, Pin Arrangement: Linear Pin Arrangement, Pin Length [P]: 3.6mm, Packaging Type: Boxed Packed

Borne for printed circuit board, rated current: 15 A, nominal section: 2.5 mm², number of potentials: 13, number of rows: 1, number of poles per row: 13, article family: BCW-X10, pitch: 5 mm, connection type: Screw connection with wire protection stirrup, screw fastening shape: H1L Philipps-Recess with longitudinal groove, Mounting: Wave welding, connection direction conductor/printed circuit board: 0°, color: whitish green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.6 mm, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

ETIM for 1304189 Connectors (EC002643)

Feature Name

Feature Value

Height (EF000040)

13.7 mm

Number of electrical connections (EF008252)

13

Number of levels (EF002659)

1

Modular spacing connections (EF006827)

5 mm

Rated current I_n (EF008250)

15 A

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Connection type conductor (EF006821)

Screw connection

Connectable conductor cross section solid-core (EF007337)

0.2 mm²

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.2 mm²

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.2 mm²

Connectable conductor cross section multi-wired (EF007343)

0.2 mm²

Connection type PCB (EF006822)

Soldering connection

Diameter connection pin (EF006823)

1.3 mm

Length pin (EF006825)

3.6 mm

Material insulation body (EF007543)

Other

Housing colour (EF000136)

Other

Inflammability class of insulation material according to UL94 (EF002521)

V0

Operating temperature (EF002393)

-40 °C

Type of banding (EF007011)

Carton (for SMD)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCW-500X10-13 GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.