

INDUSTRIAL COMPONENT DATA

BCW-500X10-15 GN 1304191 PHOENIX CONTACT Printed circuit board terminal, rated current: 15 A, rated cross-se..

Brand: PHOENIX CONTACT | Manufacturer Part Number: BCW-500X10-15 GN



Manufacturer	PHOENIX CONTACT
MPN / Reference	BCW-500X10-15 GN
Catalog number	1304191
Category	Printed circuit board terminal
Minimum order	1000 Pcs
Document ID	EO-232711A7DB
Generated	2026-08-05

Product Overview

Printed circuit board terminal, rated current: 15 A, rated cross-section: 2.5 mm², number of potentials: 15, number of rows: 1, pitch: 5 mm, connection type: Screw connection with wire protection bracket, screw clamping method: H1L Philipps-Recess with longitudinal groove, mounting: Wave soldering, conductor connection direction/printed circuit board: 0°, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.6 mm, Packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

ETIM for 1304191 Connectors (EC002643)
Feature Name
Feature Value
Height (EF000040)
13.7 mm
Number of electrical connections (EF008252)
15
Number of levels (EF002659)
1
Modular spacing connections (EF006827)
5 mm
Rated current I_n (EF008250)

15 A
Over voltage category (EF006785)
III
Pollution degree (EF006786)
2
Connection type conductor (EF006821)
Screw connection
Connectable conductor cross section solid-core (EF007337)
0.2 mm²
Connectable conductor cross section fine-strand with cable end sleeve (EF007339)
0.2 mm²
Connectable conductor cross section fine-strand without cable end sleeve (EF007341)
0.2 mm²
Connectable conductor cross section multi-wired (EF007343)
0.2 mm²
Connection type PCB (EF006822)
Soldering connection
Diameter connection pin (EF006823)
1.3 mm
Length pin (EF006825)
3.6 mm
Material insulation body (EF007543)
Other
Inflammability class of insulation material according to UL94 (EF002521)
V0
Operating temperature (EF002393)
-40 °C
Type of banding (EF007011)
Carton (for SMD)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BCW-500X10-15 GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.