

INDUSTRIAL COMPONENT DATA

RVT-AL/ST 4,8/12 3240521 PHOENIX CONTACT Blind rivets, Ø 4.8 mm, 12 mm sleeve length, aluminum sleeve, zinc-..

Brand: PHOENIX CONTACT | Manufacturer Part Number: RVT-AL/ST 4,8/12



Manufacturer	PHOENIX CONTACT
MPN / Reference	RVT-AL/ST 4,8/12
Catalog number	3240521
Category	Blind rivet
Minimum order	500 Pcs
Document ID	EO-DCE0E81E5A
Generated	2026-08-03

Product Overview

Blind rivet

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > TOOL fox
--------------	----------------------------

Additional Product Information

Key Commercial Data

Orderkey 3240521

Packing unit 500 pc

Minimum order quantity 500 pc

Note Made to Order (non-returnable)

Catalog page Page 400 (C-3-2017)

GTIN 4046356527521

Weight per Piece (excluding packing) 2.820 g

Custom tariff number 83082000

Country of origin CN (China)

Dimensions

Length (b) 12 mm

Hole diameter 4.9 mm

Diameter 4.8 mm

Max. material thickness 8 mm

Material thickness (g) 6 mm

General

Color silver

Material Aluminum (AlMg 3/3.5)/galvanized steel

Classifications

eCl@ss 10.0.123120402eCl@ss 4.021043074eCl@ss 4.121043074eCl@ss 5.023120402eCl@ss 5.123120400eCl@ss
6.023120400eCl@ss 7.023120402eCl@ss 8.023120402eCl@ss 9.023120402
ETIM 3.0EC002339ETIM 4.0EC002339ETIM 5.0EC002339ETIM 6.0EC002339
UNSPSC 6.0130211923UNSPSC 7.090127121703UNSPSC 1127121703UNSPSC 12.0127121703UNSPSC
13.231162201

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RVT-AL/ST 4,8/12 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.