


INDUSTRIAL COMPONENT DATA

RBO 8-HC 3247973 PHOENIX CONTACT Bolt connection terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: RBO 8-HC



Manufacturer	PHOENIX CONTACT
MPN / Reference	RBO 8-HC
Catalog number	3247973
Category	Feed-through terminal block
Minimum order	5 Pcs
Document ID	EO-C7DB7C7C56
Generated	2026-08-03

Product Overview

Bolt connection terminal block

Stud connection terminal, nominal voltage: 1500 V, nominal current: 192 A, number of connections: 2, number of poles: 1, connection type: Stud connection, 1st floor, Dimensioning cross-section: 70 mm², mounting class: NS 35/7.5, NS 35/15, direct screwing, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Enclosures connectivity**

Additional Product Information

Key Commercial Data

Orderkey 3247973

Packing unit 5 pc

Minimum order quantity 5 pc

Catalog page Page 544 (C-1-2017)

GTIN 4046356725071

Weight per Piece (excluding packing) 184.280 g

Custom tariff number 85369010

Country of origin CN (China)

General

Number of positions 1

Number of levels 1

Number of connections 2
Potentials 1
Nominal cross section 70 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Area of application Railway industry
Machine building
Plant engineering
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 6.27 W
Maximum load current 192 A (in case of a 70 mm² conductor cross section, the maximum load current must not be exceeded by the total current of all connected conductors.)
Nominal current I_N 192 A
Nominal voltage U_N 1500 V
Open side panel No
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection guaranteed
Finger protection guaranteed
Note regarding shock protection Touch proofness is effective only if the ring cable lug is insulated with a shrink sleeve and does not extend beyond the cover.
Result of surge voltage test Test passed
Surge voltage test setpoint 9.8 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 2.2 kV
Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed
Result of t...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RBO 8-HC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.