

INDUSTRIAL COMPONENT DATA

RW 5 3073584 PHOENIX CONTACT Bolt connection terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: RW 5



Manufacturer	PHOENIX CONTACT
MPN / Reference	RW 5
Catalog number	3073584
Category	Panel feed-through terminal block
Minimum order	10 Pcs
Document ID	EO-6E826684F4
Generated	2026-07-31

Product Overview

Bolt connection terminal block

Wall pass-through terminal, number of poles: 1, width: 16.3 mm, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Key Commercial Data

Orderkey 3073584

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

Catalog page Page 624 (C-1-2013)

GTIN 4046356368391

Weight per Piece (excluding packing) 44.640 g

Custom tariff number 85369010

Country of origin CN (China)

General

Number of levels 1

Number of connections 2

Nominal cross section 16 mm²

Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Connection in acc. with standard IEC 60947-7-1
Nominal current I_N 76 A
Maximum load current 76 A
Nominal voltage U_N 1000 V
Open side panel Yes
Number of positions 1
Dimensions
Width 16.3 mm
Pitch 16.3 mm
Plate thickness 1 mm ... 6 mm
Connection data
Note Connection bolts
Connection side outside
Connection method Bolt connection
Conductor cross section solid min. 0.1 mm²
Conductor cross section solid max. 16 mm²
Conductor cross section flexible min. 0.1 mm²
Conductor cross section flexible max. 16 mm²
Conductor cross section AWG min. 26
Conductor cross section AWG max. 6
Screw thread M5
Tightening torque, min 2.5 Nm
Tightening torque max 3 Nm
Connection side inside
Connection method Bolt connection
Standards and Regulations
Connection in acc. with standard UL
IEC 60947-7-1
DIN 46234
DIN 46237
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substan...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RW 5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.