

INDUSTRIAL COMPONENT DATA

HC-STA-B24-SLFDC-2SSM32-ELC-AL 1412870 PHOENIX CONTACT Housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-STA-B24-SLFDC-2SSM32-ELC-AL



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-STA-B24-SLFDC-2SSM32-ELC-AL
Catalog number	1412870
Category	Housing for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-4A8BE1CEE8
Generated	2026-08-03

Product Overview

Housing

B24 socket housing, for cross flange, material: Injected cast aluminum, seawater resistant, protective cap material: PC, cable outlets: 2, side, 2x M32, height: 68 mm, cable gland: without, protective cover: yes, Standard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data

Orderkey 1412870

Packing unit 1 pc

Catalog page Page 631 (C-2-2017)

GTIN 4055626061191

Weight per Piece (excluding packing) 349.000 g

Custom tariff number 85389099

Country of origin PL (Poland)

Dimensions

Height 68 mm

Width 57 mm

Length 144 mm

Ambient conditions

Degree of protection (IP) IP66 (when plugged in)

IP67 (when plugged in)

IP54 (with closed protective cover)

Ambient temperature (operation) -40 °C ... 125 °C

General

Note for contact inserts HC-B24, BB46, D64, DD108, HV10/16, M

Size B24

Housing type Box mounting bases

Color gray aluminum

Locking type for double locking latch

No. of cable outlets 2

Cable outlet lateral

Screw connection none

Type of the screw connection 2x M32

Protective cover yes

Housing material Die-cast aluminum, salt water resistant

Housing surface material uncoated

Seal material NBR, conductive

Material, protective cover PA

Assembly instructions One opening is sealed with a plastic filler plug and can be opened using a screwdriver.

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 5.127261200eCl@ss 6.027261200eCl@ss 7.027440202eCl@ss 8.027440202eCl@ss 9.027440202

ETIM 5.0EC000437ETIM 6.0EC000437

UNSPSC 13.231261501

ETIM for 1412870 Connectors (EC000437)

Feature Name

Feature Value

Width (EF000008)

57 mm

Height (EF000040)

68 mm

Depth (EF000049)

144 mm

Type of housing (EF0069...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-STA-B24-SLFDC-2SSM32-ELC-AL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.