

INDUSTRIAL COMPONENT DATA

HC-EVO-D15-SLWSC-2SSM25-PLR-BK 1411343 PHOENIX CONTACT Housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-EVO-D15-SLWSC-2SSM25-PLR-BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-EVO-D15-SLWSC-2SSM25-PLR-BK
Catalog number	1411343
Category	Housing for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-73A153C71D
Generated	2026-08-05

Product Overview

Housing

D15 socket housing, with longitudinal flange, material: PA, protective cap material: PC, cable outlets: 2, side, 2x M25, height: 52 mm, cable gland: without, protective cover: yes, Standard

D15 socket case, with lock. longitudinal, material: PA 6.6-FR, cover material: PC, cable outlets: 2, side, 2x M25, height: 52 mm, screw connection for cable: without, protective cover: yes, Standard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1411343

Packing unit 1 pc

Catalog page Page 520 (C-2-2017)

GTIN 4046356929134

Weight per Piece (excluding packing) 105.400 g

Custom tariff number 85389099

Country of origin PL (Poland)

Dimensions

Height 52 mm

Width 51 mm

Length 80 mm

Ambient conditions

Degree of protection (IP) IP66 (when plugged in or with locked protective cover)

Degree of protection (NEMA) 12 (UL 50e)

Ambient temperature (operation) -40 °C ... 125 °C

General

Note For contact inserts HC-D15, A10

Size D15

Housing type Box mounting bases

Color black

Locking type with single locking latch

No. of cable outlets 2

Cable outlet lateral

Screw connection none

Type of the screw connection 2x M25

Protective cover yes

Housing material PA

Material lock PA

Material, protective cover PA

Flammability rating according to UL 94 V0

Connection One of the two openings for the screw connections is sealed but can be broken open using a screwdriver.

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 5.127261200eCl@ss 6.027261200eCl@ss 7.027440202eCl@ss 8.027440202eCl@ss 9.027440202

ETIM 4.0EC000437ETIM 5.0EC000437ETIM 6.0EC000437

UNSPSC 13.231261501

ETIM for 1411343 Connectors (EC000437)

Feature Name

Feature Value

Width (EF000008)

51 mm

Height (EF000040)

52 mm

Depth (EF000049)

80 mm

Type of housing (EF006980)

Socket c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-EVO-D15-SLWSC-2SSM25-PLR-BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.