

INDUSTRIAL COMPONENT DATA

SACB-4/ 8-10,0PUR SCO P 1452437 PHOENIX CONTACT

Sensor/actuator box, Application: Standard, Connection metho..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACB-4/ 8-10,0PUR SCO P



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACB-4/ 8-10,0PUR SCO P
Catalog number	1452437
Category	Passive sensor-actuator interface (with cable)
Minimum order	1 Pcs
Document ID	EO-62A109EA4E
Generated	2026-08-01

Product Overview

Sensor/actuator box, Application: Standard, Connection method: M12-SPEEDCON-socket Plastic, Number of slots: 4, Number of positions: 5, Coding: A - standard, Slot assignment: Double, Status indication: No, Universal; Master cable connection: Fixed connection 180°, PUR/PVC, Cable length: 10 m, Shielding: No

Sensor/actuator box, application: Standard, connection type: SPEEDCON M12 female connector Plastic, number of plug-in stations: 4, number of poles: 5, coding: A - standard, occupation of plug-in stations: Double, status indication: No, Universal; Main cable connection: Fixed connection 180°, PUR/PVC, cable length: 10 m, shielding: no

Distributor box, application: Standard, connection method: M12-SPEEDCON-socket Plastic, number of slots: 4, number of positions: 5, coding: A, slot assignment: Double, status display: No, Universal; master cable connection: Fixed connection 180°, PUR/PVC, cable length: 10 m, shielding: no

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > QUICKON Installation System (QPD)
--------------	---

Additional Product Information

Technical dataNotesAssembly note NOTE:Observe the permissible bending radii when routing cables, since the degree of protection may be at risk if the bending forces are too high. Reduce mechanical loads upstream of the connector, e.g., by using cable ties.

Note on application Unused slots are to be sealed off prior to commissioning. Suitable sealing elements are to be found under "Accessories".

Product propertiesProduct type Distributor box

Application Standard

Number of positions 5

Number of slots 4

Coding A

LED no

Electrical propertiesNominal voltage UN 120 V AC

120 V DC

Rated current, total 12 A

Max. current carrying capacity per path 2 A

Current carrying capacity per slot 4 A

Connection dataConductor connection

Sensor/actuator connection system M12-SPEEDCON-socket

Tightening torque slot sensor/actuator cable 0.4 Nm

Tightening torque of mounting screw for fixing the housing 0.5 Nm

Pin assignment

Slot/position = Wire color or connection 1 / 4 (A) = WH

1 / 2 (B) = GYPK

2 / 4 (A) = GN

2 / 2 (B) = RDBU

3 / 4 (A) = YE

3 / 2 (B) = WHGN

4 / 4 (A) = GY

4 / 2 (B) = BNGN

1-4 / 1 (+ 120 V) = BN

1-4 / 3 (0 V) = BU

1-4 / 5 (PE) = GNYE

SignalingStatus display present No

DimensionsDimensional drawing

Width 54 mm

Height 23 mm

Length 117 mm

Material specificationsMaterial Threaded sleeve PBT

Material Housing PBT

Material Molding compound PUR

Flammability rating according to UL 94 V0

Seal material O-ring NBR

Contact material Cu alloy

Contact surface material gold-plated

Contact carrier mat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACB-4/ 8-10,0PUR SCO P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.