

INDUSTRIAL COMPONENT DATA

WP-G BRASS IP65 M10 3241058 PHOENIX CONTACT Screw connection

Brand: PHOENIX CONTACT | Manufacturer Part Number: WP-G BRASS IP65 M10



Manufacturer	PHOENIX CONTACT
MPN / Reference	WP-G BRASS IP65 M10
Catalog number	3241058
Category	Screw connection for protective metallic hose
Minimum order	10 Pcs
Document ID	EO-83ECF9E640
Generated	2026-08-04

Product Overview

Screw connection
Brass cable gland with metric thread, IP65 degree of protection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data
Orderkey 3241058
Packing unit 10 pc
Minimum order quantity 10 pc
Note Made to Order (non-returnable)
Catalog page Page 644 (C-3-2017)
GTIN 4046356712088
Weight per Piece (excluding packing) 14.320 g
Custom tariff number 74122000
Country of origin DE (Germany)
Dimensions
Length (b) 31 mm
Width (a) 19 mm
Height (c) 31 mm

Wrench size 15 mm

Inner diameter (f) 6 mm

Outside diameter 10 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 125 °C

Degree of protection IP65

General

Color brass

Type Straight

Outer thread

Components halogen-free

Material Brass

Classifications

eCl@ss 4.027141209eCl@ss 4.127141209eCl@ss 5.021132007eCl@ss 5.121132000eCl@ss 6.021132000eCl@ss

7.027439203eCl@ss 8.027439203eCl@ss 9.027430310

ETIM 3.0EC000519ETIM 4.0EC000519ETIM 5.0EC001180ETIM 6.0EC001180

UNSPSC 6.0130211812UNSPSC 7.090139121410UNSPSC 1139121411UNSPSC 12.0139121411UNSPSC

13.240141734

ETIM for 3241058 Flexible conduit systems (EC001180)

Feature Name

Feature Value

Nominal diameter (EF005114)

6 mm

Revolving thread (EF001757)

No

Connection type to housing (EF008847)

Thread

Thread type (EF001758)

Metric

Thread connection size (EF007834)

Other

One-piece (EF001774)

No

Housing material (EF001596)

Other

Surface protection (EF000139)

Nickel-plated

Lowest inner diameter hose (EF001760)

7 mm

Max. outer diameter hose (EF002504)

10 mm

Thread length (EF000368)

10 mm

Total length (EF000369)

31 mm

Total height (EF001761)

31 mm

Approved in combination with protective conduit acco...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WP-G BRASS IP65 M10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.