

**INDUSTRIAL COMPONENT DATA**

# WP-G BRASS IP65 M25 3241062 PHOENIX CONTACT Screw connection

Brand: PHOENIX CONTACT | Manufacturer Part Number: WP-G BRASS IP65 M25

PRODUCT IMAGE\nNOT  
AVAILABLE

|                 |                                               |
|-----------------|-----------------------------------------------|
| Manufacturer    | PHOENIX CONTACT                               |
| MPN / Reference | WP-G BRASS IP65 M25                           |
| Catalog number  | 3241062                                       |
| Category        | Screw connection for protective metallic hose |
| Minimum order   | 10 Pcs                                        |
| Document ID     | EO-0FD062A332                                 |
| Generated       | 2026-08-04                                    |

## Product Overview

Screw connection  
Brass cable gland with metric thread, IP65 degree of protection  
Brass cable gland with metric thread, IP65 rating

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; Industrial plug-in connectors/interfaces

## Additional Product Information

Key Commercial Data  
Orderkey 3241062  
Packing unit 10 pc  
Minimum order quantity 10 pc  
Note Made to Order (non-returnable)  
Catalog page Page 644 (C-3-2017)  
GTIN 4046356712125  
Weight per Piece (excluding packing) 73.890 g  
Custom tariff number 74122000  
Country of origin DE (Germany)  
Dimensions  
Length (b) 41 mm  
Width (a) 39 mm

Height (c) 41 mm  
Wrench size 34 mm  
Inner diameter (f) 20.5 mm  
Outside diameter 27 mm  
Ambient conditions  
Ambient temperature (operation) -40 °C ... 125 °C  
Degree of protection IP65  
General  
Color brass  
Type Straight  
Outer thread  
Components halogen-free  
Material Brass  
Classifications  
eCl@ss 4.027141209eCl@ss 4.127141209eCl@ss 5.021132007eCl@ss 5.121132000eCl@ss 6.021132000eCl@ss  
7.027439203eCl@ss 8.027439203eCl@ss 9.027430310  
ETIM 3.0EC000519ETIM 4.0EC000519ETIM 5.0EC001180ETIM 6.0EC001180  
UNSPSC 6.0130211812UNSPSC 7.090139121410UNSPSC 1139121411UNSPSC 12.0139121411UNSPSC  
13.240141734  
ETIM for 3241062 Flexible conduit systems (EC001180)  
Feature Name  
Feature Value  
Nominal diameter (EF005114)  
20.5 mm  
Revolving thread (EF001757)  
No  
Connection type to housing (EF008847)  
Thread  
Thread type (EF001758)  
Metric  
Thread connection size (EF007834)  
Other  
One-piece (EF001774)  
No  
Housing material (EF001596)  
Other  
Surface protection (EF000139)  
Nickel-plated  
Lowest inner diameter hose (EF001760)  
22 mm  
Max. outer diameter hose (EF002504)  
27 mm  
Thread length (EF000368)  
11 mm  
Total length (EF000369)  
41 mm  
Total height (EF001761)

41 mm

Approved in combination with protective condu...

### REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WP-G BRASS IP65 M25 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

#### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.