

INDUSTRIAL COMPONENT DATA

WP-GT BRASS PG11 3241025 PHOENIX CONTACT Screw connection

Brand: PHOENIX CONTACT | Manufacturer Part Number: WP-GT BRASS PG11



Manufacturer	PHOENIX CONTACT
MPN / Reference	WP-GT BRASS PG11
Catalog number	3241025
Category	Screw connection for protective metallic hose
Minimum order	10 Pcs
Document ID	EO-1B5C6E3C04
Generated	2026-08-01

Product Overview

Screw connection

Brass cable gland with rotating Pg thread, IP40 degree of protection

Cable gland made from brass with Pg thread, rotatable, IP40 protection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Technical dataProduct propertiesProduct type Corrugated pipe screw connection

Type of the screw connection Conduit adapter

Type Outer thread

Cable outlet straight

Thread type Pg

Data management status

Article revision 00

DimensionsWidth 25 mm

Height 30 mm

Length 30 mm

Wrench size 23 mm

Wrench size for mounting 23 mm

External dimensions

Outside diameter 17 mm

Internal dimensions

Internal diameter 11.5 mm

Material specificationsColor Brass color

Material Brass, nickel-plated

Material for screw connection Brass, nickel-plated

Components halogen-free

Mechanical propertiesMechanical data

Type of the screw connection Conduit adapter

Environmental and real-life conditionsAmbient conditions

Degree of protection IP40

Ambient temperature (operation) -40 °C ... 250 °C

ETIM for 3241025 Flexible conduit systems (EC001180)

Feature Name

Feature Value

Nominal diameter (EF005114)

11.5 mm

Revolving thread (EF001757)

No

Connection type to housing (EF008847)

Thread

Thread type (EF001758)

Other

Thread connection size (EF007834)

Other

One-piece (EF001774)

No

Housing material (EF001596)

Other

Surface protection (EF000139)

Nickel-plated

Lowest inner diameter hose (EF001760)

13 mm

Max. outer diameter hose (EF002504)

17 mm

Thread length (EF000368)

7 mm

Total length (EF000369)

30 mm

Total height (EF001761)

30 mm

Approved in combination with protective conduit according to DIN EN 61386-23 (EF008142)

No

Approved in combination with protective conduit CSA (EF001765)

No

Approved in combination with protec...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WP-GT BRASS PG11 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.