

**INDUSTRIAL COMPONENT DATA**

# FBSK 4-10 1928411 PHOENIX CONTACT Plug-in bridge

Brand: PHOENIX CONTACT | Manufacturer Part Number: FBSK 4-10



|                 |                                                   |
|-----------------|---------------------------------------------------|
| Manufacturer    | PHOENIX CONTACT                                   |
| MPN / Reference | FBSK 4-10                                         |
| Catalog number  | 1928411                                           |
| Category        | Accessories/spare parts for industrial connectors |
| Minimum order   | 50 Pcs                                            |
| Document ID     | EO-3922400B7C                                     |
| Generated       | 2026-07-31                                        |

## Product Overview

Plug-in bridge

Jumper, insulated, 10 mm pitch, 4-pole

Bridge, fully insulated, pitch 10 mm, 4-pos.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                        |
|--------------|----------------------------------------|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |
|--------------|----------------------------------------|

## Additional Product Information

Technical dataProduct propertiesProduct type Bridge

Product family FBSK

Product line COMBICON Terminals Special

Number of positions 4

Pitch 10 mm

Number of connections 4

Number of rows 1

Number of potentials 4

Data management status

Article revision 02

DimensionsPitch 10 mm

Material specificationsMaterial data - contact

Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201

Contact material Cu alloy

Material data - housing  
Color (Housing) red (3001)  
Insulating material PA  
Insulating material group I  
CTI according to IEC 60112 600  
Flammability rating according to UL 94 V0  
Glow wire flammability index GWFI according to EN 60695-2-12 850  
Glow wire ignition temperature GWIT according to EN 60695-2-13 775  
Temperature for the ball pressure test according to EN 60695-10-2 125 °C  
ConnectorConnection 1  
Insulating material PA  
CTI according to IEC 60112 600

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FBSK 4-10 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.