

## INDUSTRIAL COMPONENT DATA

## FBSK 4-7,5 1928369 PHOENIX CONTACT Plug-in bridge

Brand: PHOENIX CONTACT | Manufacturer Part Number: FBSK 4-7,5



|                 |                                                   |
|-----------------|---------------------------------------------------|
| Manufacturer    | PHOENIX CONTACT                                   |
| MPN / Reference | FBSK 4-7,5                                        |
| Catalog number  | 1928369                                           |
| Category        | Accessories/spare parts for industrial connectors |
| Minimum order   | 10 Pcs                                            |
| Document ID     | EO-76BE8087F2                                     |
| Generated       | 2026-08-03                                        |

## Product Overview

Plug-in bridge

Bridge, insulated, 7.5 mm pitch, 4-pole

Bridge, fully insulated, pitch 7.5 mm, 4-pos.

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

|              |                                        |
|--------------|----------------------------------------|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |
|--------------|----------------------------------------|

## Additional Product Information

Technical dataProduct propertiesProduct type Bridge

Product family FBSK

Product line COMBICON Terminals Special

Number of positions 4

Pitch 7.5 mm

Number of connections 4

Number of rows 1

Number of potentials 4

Data management status

Article revision 03

DimensionsPitch 7.5 mm

Material specificationsMaterial data - contact

Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201

Contact material Cu alloy

Material data - housing

Color (Housing) red (3001)

Insulating material PA

Insulating material group I

CTI according to IEC 60112 600

Flammability rating according to UL 94 V0

Glow wire flammability index GWFI according to EN 60695-2-12 850

Glow wire ignition temperature GWIT according to EN 60695-2-13 775

Temperature for the ball pressure test according to EN 60695-10-2 125 °C

ConnectorConnection 1

Insulating material PA

CTI according to IEC 60112 600

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FBSK 4-7,5 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.